





## M26L - HEDRA 93008 DIM5

23251 9315 BBR

AVAILABLE IN  
**BLACK BRONZE** 23251 9315 BBR  
**GOLD COLOURED** 23251 9315 GC



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Low voltage systems Low voltage system mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.4
<b>ADJUSTABILITY</b>	0° to 90° swiveling, 355° rotatable
<b>INFORMATION</b>	LENS SP-8° EXCL.LED POWER SUPPLY 48V-DC

### Electrical info

<b>ELECTRICAL</b>	48V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	DALI
<b>ENERGY CLASS</b>	F
<b>CERTIFICATES</b>	CB, ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 5,7W / CRI>90 (R9: 55) / 3000K / 519lm
<b>TM-30 VALUES</b>	rf: 92 / Rg: 98
<b>SDCM</b>	SDCM2
<b>RISKGROUP</b>	RG2 (threshold 0,6m)
<b>LM80</b>	L90B10 > 41000
<b>BEAMANGLE</b>	8°
<b>LED TECHNICS (LIGHT SOURCE)</b>	519lm // 5,7W // 90lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	397lm // 6,6W // 61lm/W

### Remarks

Take a look at our **MAGNETIC PROFILES** movie

### Requirements

VIZIR TUBE  
 LED POWER SUPPLY 48V-DC

### Accessories

VIZIR HONEYCOMB  
 VIZIR SOFTENING LENS

# DELTALIGHT

## M26L - HEDRA 93008 DIM5


23251 9315 BBR

For detailed installation instructions, please consult the manual : [23251\\_XXXX\\_HAND.pdf](#)


### FINISH YOUR SPECIFICATION

#### LED power supplies

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

14


Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

34

Dimtype: non-dimmable




**21012 0230** LED POWER SUPPLY 48V-DC / 100W

14

Dimtype: non-dimmable

Cutout dimension (mm): 40




**21012 0240** LED POWER SUPPLY 48V-DC / 200W

29


Dimtype: non-dimmable

Cutout dimension (mm): 40

#### Light altering devices



**473 03 01 B** VIZIR HONEYCOMB B




**473 03 04** VIZIR SOFTENING LENS

# DELTALIGHT

## M26L - HEDRA 93008 DIM5

23251 9315 BBR

### Finish your product



**473 01 00 B** VIZIR TUBE B



**473 01 00 FBR** VIZIR TUBE FBR



**473 01 00 FG** VIZIR TUBE FG




**473 01 00 W** VIZIR TUBE W




## COMPATIBLE COMPOSABLES

### SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)


### Available Colours




**23358 0000** SLM26L - PROFILE



**23358 0010** SLM26L - PROFILE 1m



**23358 0020** SLM26L - PROFILE 2m




**23358 0030** SLM26L - PROFILE 3m



### SHIFTLINE M35R profile

### Available Colours




**23375 0000** SLM35R - PROFILE




# DELTALIGHT

## M26L - HEDRA 93008 DIM5


23251 9315 BBR



**23375 0010** SLM35R - PROFILE 1m



**23375 0020** SLM35R - PROFILE 2m



**23375 0030** SLM35R - PROFILE 3m



Notes: