





M52 - 1 LED 82720 MDL

421 218 1822 MDL



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	non adjustable
INFORMATION	LENS FL-20° EXCL.LED POWER SUPPLY 48V-DC
Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>80 / 2700K / 558lm
SDCM	SDCM2
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	558lm // 6W // 94lm/W
LED TECHNICS (LUMINAIRE)	474lm // 6,9W // 69lm/W
Requirements	
LED POWER SUPPLY 48V-DC	
Options	
DIMMABLE MODULATOR	

For detailed installation instructions, please consult the manual : [421_218_1XXX_MDL_HAND.pdf](#)

M52 - 1 LED 82720 MDL

421 218 1822 MDL

FINISH YOUR SPECIFICATION


Current supply

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21032 0030 SMART 48 MODULATOR PLUG-IN WD

27

Dimtype: WDL = wireless dimmable


SMART 48

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

27

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

27

Dimtype: WDL = wireless dimmable


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 89 48 90 LED POWER SUPPLY 48V-DC / 90W

13

Dimtype: non-dimmable

Cutout dimension (mm): 75



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN





14

Dimtype: non-dimmable





DELTALIGHT

M52 - 1 LED 82720 MDL

421 218 1822 MDL

	300 89 48 150 LED POWER SUPPLY 48V-DC / 150W	21	☐
Dimtype: non-dimmable			
	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	34	☐
Dimtype: non-dimmable			
	21012 0230 LED POWER SUPPLY 48V-DC / 100W	14	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 40			
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	29	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 40			

COMPATIBLE COMPOSABLES

SPLITLINE M52 profile		Available Colours
	<u>420 52 10 00</u> SPM52 - PROFILE 1m	☒
	<u>420 52 20 00</u> SPM52 - PROFILE 2m	☒
	<u>420 52 30 00</u> SPM52 - PROFILE 3m	☒
	<u>24413 0000</u> SPM52 - PROFILE	☒

DELTALIGHT

M52 - 1 LED 82720 MDL

421 218 1822 MDL

Notes: