
DELTALIGHT




MINIGRID ON 350 92750 DIM8

REFERENCE 100046 9238 B-W

AVAILABLE IN
BLACK-BLACK 100046 9238 B-B
BLACK-WHITE 100046 9238 B-W
WHITE-BLACK 100046 9238 W-B
WHITE-WHITE 100046 9238 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.6
ADJUSTABILITY	0° to 20° swiveling, 350° rotatable
INFORMATION	3 x REFLECTOR FL-50° INCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	3 x (LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm)
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	50°
LED TECHNICS (LIGHT SOURCE)	3123lm // 25,8W // 121lm/W
LED TECHNICS (LUMINAIRE)	2513lm // 29,7W // 85lm/W

For detailed installation instructions, please consult the manual : **100046_XXX8_HAND.pdf**


DELTALIGHT

MINIGRID ON 350 92750 DIM8

100046 9238 B-W

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40

Notes: