



SPY 20 L CLIP 2 93030

27216 9320 B-B

AVAILABLE IN

BLACK-BLACK 27216 9320 B-B



FLEMISH BRONZE-BLACK 27216 9320 FBR-B

FLEMISH GOLD-BLACK 27216 9320 FG-B

FULL WHITE 27216 9320 FW

GOLD COLORED-BLACK 27216 9320 GC-B

WHITE-WHITE 27216 9320 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Semi-recessed
CUTOUT SHAPE/SIZE (MM)	round - 62
RECESSED DEPTH (MM)	40
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCLLED POWER SUPPLY 350-1050mA-DC SPY 20 TUBE B included

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED array 1-3,1W / CRI>90 (R9: 60) / 3000K / 131-334lm)
TM-30 VALUES	rf: 92 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 150000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	668lm // 6,2W // 109lm/W
LED TECHNICS (LUMINAIRE)	503lm // 7,1W // 71lm/W

Requirements

LED POWER SUPPLY 350 / 500 / 700 / 1050mA-DC DIM

For detailed installation instructions, please consult the manual : [27216_XXX0_HAND.pdf](#)

DELTALIGHT

SPY 20 L CLIP 2 93030

27216 9320 B-B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Wood	-
 Concrete	-
 Hollow-core slab	-
 Stretched ceiling	-
	 29810 0080 - MOUNTING KIT NO AIR 104 Required
	 29810 0100 - MOUNTING KIT SIDE AIR ONLY 1 Required
	 29810 0040 - MOUNTING KIT SIDE AIR 104 Required
	 29810 0080 - MOUNTING KIT NO AIR 104 Required
	 29810 0200 - MOUNTING KIT TOP AIR ONLY 1 Required
	 29810 0240 - MOUNTING KIT TOP AIR 104 Required

FINISH YOUR SPECIFICATION


LED power supplies

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the 'I' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1

2->7

Dimtype: 1-10V

Cutout dimension (mm): 30



300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2->7



Dimtype: DALI

Cutout dimension (mm): 45

DELTALIGHT







SPY 20 L CLIP 2 93030

27216 9320 B-B

	300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL	2->7 ☐
	Dimtype: non-dimmable	
	Cutout dimension (mm): 30	
	300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL	2->7 ☐
	Dimtype: WDL = wireless dimmable	
	Cutout dimension (mm): 45	
	300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1	2->7 ☐
	Dimtype: 1-10V	
	Cutout dimension (mm): 30	
	300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	2->7 ☐
	Dimtype: DALI	
	Cutout dimension (mm): 45	
	300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL	2->7 ☐
	Dimtype: non-dimmable	
	Cutout dimension (mm): 30	
	300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL	2->7 ☐
	Dimtype: WDL = wireless dimmable	
	Cutout dimension (mm): 45	
	300 48 700 ED1 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1	2->7 ☐
	Dimtype: 1-10V	
	Cutout dimension (mm): 30	
	300 48 700 ED5 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5	2->7 ☐
	Dimtype: DALI	
	Cutout dimension (mm): 45	
	300 48 700 MDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL	2->7 ☐
	Dimtype: non-dimmable	
	Cutout dimension (mm): 30	
	300 48 700 WDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL	2->7 ☐
	Dimtype: WDL = wireless dimmable	
	Cutout dimension (mm): 45	

SPY 20 L CLIP 2 93030











27216 9320 B-B

	300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 Dimtype: mains (phase cut-off) or push button Cutout dimension (mm): 56	8 8 8	☐
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 82	13(12) 12(12) 12(9) 9(6)	☐
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 72	2->9(7) 8(5) 8(3)	☐
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 Dimtype: 1-10V or DALI or push button	2->7 2->7 2->7	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Cutout dimension (mm): 72	8(7) 8(5) 7(3) -	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 84	4->20(19) 20(14) 14(14) -	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 55	3->8(7) 7(5) 5(3)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	2->8(7) 7(5) 4(3)	☐
	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non-dimmable Cutout dimension (mm): 90	9->14 6->14 5->15 5->11	☐
	300 90 136 LED POWER SUPPLY MULTI-POWER HC DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 90	7(6)	☐

DELTALIGHT

SPY 20 L CLIP 2 93030











27216 9320 B-B

	300 90 148 LED POWER SUPPLY 1050mA-DC / 22W Dimtype: non-dimmable Cutout dimension (mm): 48	3(!) ☐
	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non-dimmable Cutout dimension (mm): 50	3->7 2->7 2->7 2->6 ☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1-10V Cutout dimension (mm): 54	2->9 2->9 2->8 2->6 ☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	2->8 2->9 2->9 2->6 ☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 84	12(12) 12(12) 12(10) 10(6) ☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 54	2->9 2->9 2->8 2->6 ☐
	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 50	4->5 ☐
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 50	5->7 ☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 55	3->5 3->4 ☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 55	6->9 6->8 ☐

DELTALIGHT

SPY 20 L CLIP 2 93030

27216 9320 B-B

	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 48	2->7 2->7 2->4	☐
	21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 40	3->3	☐
	21012 0318 LED POWER SUPPLY 500mA / 10W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 40	3->3	☐
	21012 0328 LED POWER SUPPLY 700mA / 15W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 40	3->3	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68 Dimtype: non-dimmable Cutout dimension (mm): 60	8(7)	☐
	21012 0490 LED POWER SUPPLY 700mA-DC / 30W IP68 Dimtype: non-dimmable Cutout dimension (mm): 60	7(3)	☐
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68 Dimtype: non-dimmable Cutout dimension (mm): 60	8(5)	☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 30	2->7	☐
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 Dimtype: DALI Cutout dimension (mm): 30	2->7	☐
	21032 0315 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5 Dimtype: DALI Cutout dimension (mm): 30	2->7	☐

DELTALIGHT

SPY 20 L CLIP 2 93030

27216 9320 B-B

Notes: