



M26L - SPY 391 92740 MDL

23258 9230 BRG

AVAILABLE IN

SCHWARZ 23258 9230 B

ALU GEBÜRSTET 23258 9230 BRA

GEBÜRSTETES ANTHRAZIT 23258 9230 BRAT

GEBÜRSTETES KUPFER 23258 9230 BRCU

GEBÜRSTETES GOLD 23258 9230 BRG

GEBÜRSTETE ALTE BRONZE 23258 9230 BROB



FLEMISH BRONZE 23258 9230 FBR

FLEMISH GOLD 23258 9230 FG

GOLDFARBEN 23258 9230 GC

KLAVIER SCHWARZ 23258 9230 PB

WEISS 23258 9230 W



[View on website](#)



General info

LOCATION	innenbereich
INSTALLATION	Niederspannungssysteme Niederspannungssysteme montiert
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° schwenkbar, 360° drehbar
INFORMATION	REFLECTOR WFL-40° EXCL.LED POWER SUPPLY 48V-DC

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V, DALI / Taster
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 60) / 2700K / 1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	844lm // 9,9W // 85lm/W

Remarks

Take a look at our **MAGNETIC PROFILES** movie

Requirements

SPY 39 TUBE or VISOR 39

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

Delta Light NV may revise the information and technical data at any time without notice. Version: 28/08/2026

For detailed installation instructions, please consult the manual : [23258_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

Stromversorgung

of Fixtures

Min current | Max current

of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



21032 0030 SMART 48 MODULATOR PLUG-IN WD

Dimtype: WDL = Drahtlos dimmbar


19

SMART 48

of Fixtures

Min current | Max current


of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 90 011 SMART 48 MODULATOR DIM9

Dimtype: 1-10V, DALI / Taster

19



300 90 012 SMART 48 MODULATOR WD

Dimtype: WDL = Drahtlos dimmbar


19

LED Betriebsgeräte

of Fixtures

Min current | Max current

of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN


Dimtype: nicht dimmbar

10

DELTALIGHT

M26L - SPY 391 92740 MDL

23258 9230 BRG




300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN

24

☐

Dimtype: nicht dimmbar




21012 0230 LED POWER SUPPLY 48V-DC / 100W

10

☐

Dimtype: nicht dimmbar

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W


20

☐

Dimtype: nicht dimmbar

Cutout dimension (mm): 40

Licht veredelndes Zubehör



24144 0030 B VISOR 39 B

☐

Beenden Sie Ihr Produkt



24144 0010 B SPY 39 TUBE B

☐

24144 0010 FBR SPY 39 TUBE FBR

☐

24144 0010 FC SPY 39 TUBE FC

☐

24144 0010 GC SPY 39 TUBE GC

☐

24144 0010 W SPY 39 TUBE W

☐

24144 0070 SPY 39 TUBE SBL










☐

DELTALIGHT

M26L - SPY 391 92740 MDL

23258 9230 BRG


COMPATIBLE COMPOSABLES

SHIFTLINE M26L FLOOR		Available Colours
	29321 0010 SLM26L F MDL	
	29322 002W SLM26L F MDL WD	
SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)		Available Colours
	23358 0000 SLM26L - PROFILE	 
	23358 0010 SLM26L - PROFILE 1m	 
	23358 0020 SLM26L - PROFILE 2m	         
	23358 0030 SLM26L - PROFILE 3m	         
SHIFTLINE M35R profile		Available Colours
	23375 0000 SLM35R - PROFILE	
	23375 0010 SLM35R - PROFILE 1m	
	23375 0020 SLM35R - PROFILE 2m	

DELTALIGHT

M26L - SPY 391 92740 MDL

23258 9230 BRG



23375 0030 SLM35R - PROFILE 3m



Notes: