
DELTALIGHT




D-LINER 30 INF LOC2 1114 93058 DIM5

REFERENCE 32085 9325 W-W

AVAILABLE IN
BLACK-BLACK 32085 9325 B-B
WHITE-WHITE 32085 9325 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
INGRESS PROTECTION	IP20
WEIGHT (KG)	0
ADJUSTABILITY	non adjustable
INFORMATION	48 x REFLECTOR FL-58° INCL.DIMMABLE LED POWER SUPPLY 520mA-DC INCL.1 x CABLE 5 x 0,75mm² - 0,5m + WIELAND PLUG GST18i5 male pastelblue

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	C
CERTIFICATES	EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 17,3W / CRI>90 / 3000K / 3058lm
LED TECHNICS (LIGHT SOURCE)	3058lm // 17,3W // 177lm/W
LED TECHNICS (LUMINAIRE)	2419lm // 20W // 122lm/W

For detailed installation instructions, please consult the manual : **32085_XXX5_HAND.pdf**

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
Acoustic climate-control ceiling Hunter Douglas 30BD	-

DELTALIGHT

D-LINER 30 INF LOC2 1114 93058 DIM5

32085 9325 W-W

Notes: