



COMPO S HP 92741

9 15719 9230 B


AVAILABLE IN

NEGRO 9 15719 9230 B

CHROMO 9 15719 9230 C

CHROMO OSCURO 9 15719 9230 DC

BLANCO 9 15719 9230 W



[View on website](#)



General info

LOCATION	interior
INSTALLATION	Techo Empotrado
CUTOUT SHAPE/SIZE (MM)	redondo - 120
RECESSED DEPTH (MM)	114
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.166
ADJUSTABILITY	0° to 30° giratorio, 355° orientable

Electrical info

CLASS	III
DIM TYPE	dependiendo del tipo de fuente de alimentación externa
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9,3W / CRI>90 / 2700K / 880lm
SDMC	SDCM2
RISKGROUP	RG1
BEAMANGLE	40°
LED TECHNICS (LIGHT SOURCE)	880lm // 9,3W // 96lm/W
LED TECHNICS (LUMINAIRE)	668lm // 10,7W // 62lm/W

Requirements

LED POWER SUPPLY 500 mA - DC

Accessories

COMPO S HONEYCOMB SINGLE USE B

COMPO S LINEAR SPREAD LENS

COMPO S SPREAD LENS

COMPO S SOFTENING LENS

COMPO S GLASS SBL

For detailed installation instructions, please consult the manual : [9_15719_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
 Plasterboard	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
 Wood	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required

FINISH YOUR SPECIFICATION

Fuente de alimentación LED	# of Fixtures
 web2print_power_supply_info_box	Min current Max current
15710 3100 LED POWER SUPPLY 18W NO DIM 1400mA	1->4 ☐
15710 3400 LED POWER SUPPLY MULTIPOWER 25W NO DIM 500mA	1->2 ☐
15710 3900 LED POWER SUPPLY MULTIPOWER 10W DIM8 500mA	1 ☐
15710 4600 LED POWER SUPPLY MULTIPOWER 12W DIM1 500mA	1 ☐
15710 5000 LED POWER SUPPLY MULTIPOWER 55W DALI DT6 1400mA Dimtype: con DALI	1->13 ☐
15710 5400 LED POWER SUPPLY MULTIPOWER 20W DALI DT6 500mA Dimtype: con DALI	1->2 ☐

Mounting Kit

 15710 0010 B MOUNTING KIT COMPO S TRIM B	☐
15710 0010 W MOUNTING KIT COMPO S TRIM W	☐

COMPO S HP 92741

9 15719 9230 B



15710 0040 MOUNTING KIT COMPO S TRIMLESS

☐

Cutout dimension (mm): 55

Dispositivos de modificación de Luz

15710 0100 B COMPO S HONEYCOMB SINGLE USE B

☐

15710 0110 COMPO S LINEAR SPREAD LENS

☐

Cutout dimension (mm): 26,5

15710 0120 COMPO S SPREAD LENS

☐

Cutout dimension (mm): 26,5

15710 0130 COMPO S SOFTENING LENS

☐

Cutout dimension (mm): 26,5

15710 0140 COMPO S GLASS SBL

☐

Cutout dimension (mm): 26,5

Notes: