



## SL19 - SPY 20 L 92730 MDL

27028 9220 B

AVAILABLE IN



**BLACK** 27028 9220 B

**FLEMISH BRONZE** 27028 9220 FBR

**FLEMISH GOLD** 27028 9220 FG

**GOLD COLOURED** 27028 9220 GC

**WHITE** 27028 9220 W



[View on website](#)



### General info

|                           |                                                                           |
|---------------------------|---------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                    |
| <b>INSTALLATION</b>       | Low voltage systems Low voltage system mounted                            |
| <b>INGRESS PROTECTION</b> | IP20                                                                      |
| <b>WEIGHT (KG)</b>        | 0.1                                                                       |
| <b>ADJUSTABILITY</b>      | 0° to 90° swiveling, 355° rotatable                                       |
| <b>INFORMATION</b>        | REFLECTOR FL-30°<br>EXCLLED POWER SUPPLY 48V-DC<br>SPY 20 TUBE B included |

### Electrical info

|                     |                                    |
|---------------------|------------------------------------|
| <b>ELECTRICAL</b>   | 48V-DC                             |
| <b>CLASS</b>        | III                                |
| <b>DIM TYPE</b>     | MDL = 1-10V or DALI or push button |
| <b>ENERGY CLASS</b> | E                                  |
| <b>CERTIFICATES</b> | CB, ENEC                           |

### Lightsource info

|                                    |                                                |
|------------------------------------|------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                            |
| <b>LIGHTSOURCE</b>                 | LED array 2W / CRI>90 (R9: 55) / 2700K / 220lm |
| <b>TM-30 VALUES</b>                | rf: 91 / Rg: 100                               |
| <b>SDCM</b>                        | SDCM3                                          |
| <b>RISKGROUP</b>                   | RG2                                            |
| <b>LM80</b>                        | L90B10 > 150000                                |
| <b>BEAMANGLE</b>                   | 30°                                            |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 220lm // 2W // 110lm/W                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 166lm // 2,3W // 72lm/W                        |

### Requirements

LED POWER SUPPLY 48V-DC

### Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : [27028\\_XXX0\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION


#### SMART 48

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 90 011** SMART 48 MODULATOR DIM9

72

Dimtype: 1-10V or DALI or push button



**300 90 012** SMART 48 MODULATOR WD

72

Dimtype: WDL = wireless dimmable


#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

37


Dimtype: non-dimmable



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

90

Dimtype: non-dimmable




**21012 0230** LED POWER SUPPLY 48V-DC / 100W

37

Dimtype: non-dimmable

Cutout dimension (mm): 40



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

75

Dimtype: non-dimmable

Cutout dimension (mm): 40


# DELTALIGHT

## SL19 - SPY 20 L 92730 MDL


27028 9220 B

### COMPATIBLE COMPOSABLES

| SHIFTLINE 19 profile | Available Colours |
|----------------------|-------------------|
|----------------------|-------------------|



**27011 0050** SL19 - PROFILE 2m



**27011 0060** SL19 - PROFILE 3m



Notes: