



SL19 - SPY 39 FOCUS 930 DIM5

27037 9305 B

AVAILABLE IN


BLACK 27037 9305 B

FLEMISH BRONZE 27037 9305 FBR


FLEMISH GOLD 27037 9305 FG

GOLD COLOURED 27037 9305 GC

WHITE 27037 9305 W



0-85°/355°



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	ADJUSTABLE BEAM 15°-45°

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1018lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	15°-45°
LED TECHNICS (LIGHT SOURCE)	1018lm // 8,6W // 118lm/W
LED TECHNICS (LUMINAIRE)	303lm // 9,9W // 31lm/W

Requirements

LED POWER SUPPLY 48V-DC

For detailed installation instructions, please consult the manual : [27037_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
5510090 3008948100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable		10
63114125 3008948240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable		24
1729830 210120230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40		10
2239230 210120240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40		20

COMPATIBLE COMPOSABLES

SHIFTLINE 19 profile	Available Colours
1910 270110060 SL19 - PROFILE 3m	

Notes: