DELTALIGHT

SPY 66 CLIP TW 96545

REFERENCE 24622 9030 B-B

AVAILABLE IN
BLACK-BLACK 24622 9030 B-B
FULL WHITE 24622 9030 FW
WHITE-WHITE 24622 9030 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Semi-recessed
CUTOUT SHAPE/SIZE (MM)	round - 51
RECESSED DEPTH (MM)	40
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8) Optional REFLECTORS 18° & 30° available

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	45°
LED TECHNICS (LIGHT SOURCE)	1087lm // 9W // 121lm/W
LED TECHNICS (LUMINAIRE)	746lm // 10,4W // 72lm/W

Requirements

SPY 66 TUBE
LED POWER SUPPLY 500mA-DC TW

Options

MOUNTING KIT FLUSH SPY

Accessories

HONEYCOMB 57
SPREAD LENS 57
LINEAR SPREAD LENS 57
SOFTENING LENS 57
GLASS SBL 57

DELTALIGHT

SPY 66 CLIP TW 96545

24622 9030 B-B

For detailed installation instructions, please consult the manual : **24622_XXX0_HAND.pdf**

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
System ceiling	414 90 01 - MOUNTING KIT FLUSH SPY	Required
Plasterboard	414 90 01 - MOUNTING KIT FLUSH SPY	Required
Stucanet	414 90 01 - MOUNTING KIT FLUSH SPY	Required
Wood	-	
Concrete	-	
Concrete + plaster	414 90 01 - MOUNTING KIT FLUSH SPY	Required
Lintel + plaster	414 90 01 - MOUNTING KIT FLUSH SPY	Required
Hollow-core slab	-	
Hollow-core slab + plaster	414 90 01 - MOUNTING KIT FLUSH SPY	Required
Stretched ceiling	-	

DELTALIGHT

SPY 66 CLIP TW 96545

24622 9030 B-B

FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5 — 2

Dimtype: DALI

Cutout dimension (mm): 85

Mounting kits



414 90 01 MOUNTING KIT FLUSH SPY

Cutout dimension (mm): 83

Light altering devices



24611 0150 B HONEYCOMB 57 SINGLE USE B



24611 0160 GLASS SBL 57



24611 0170 LINEAR SPREAD LENS 57



24611 0190 SOFTENING LENS 57

SPY 66 CLIP TW 96545

24622 9030 B-B



24611 0200 SPREAD LENS 57



24611 0210 B HONEYCOMB 57 DOUBLE USE B

Finish your product



24611 0100 B SPY 66 TUBE B

24611 0100 FBR SPY 66 TUBE FBR

24611 0100 FG SPY 66 TUBE FG

24611 0100 GC SPY 66 TUBE GC

24611 0100 W SPY 66 TUBE W

Replaceable reflector / lens

24611 0220 SPY 66 REFLECTOR 18°

24611 0230 SPY 66 REFLECTOR 30°

24611 0240 SPY 66 REFLECTOR 45°

SPY 66 CLIP TW 96545

24622 9030 B-B

Notes: