





## SPY 66 ON TW 96518

24624 9010 B

AVAILABLE IN  
**BLACK** 24624 9010 B  
**FULL WHITE** 24624 9010 FW  
**WHITE** 24624 9010 W



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Ceiling Surface mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.6
<b>ADJUSTABILITY</b>	0° to 90° swiveling, 355° rotatable
<b>INFORMATION</b>	REFLECTOR SP-18° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8) Optional REFLECTORS 30° & 45° available

### Electrical info

<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, ENEC, LCA

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 9W / CRI>90 (R9: 50) / 2700K-6500K / 1087lm
<b>TM-30 VALUES</b>	rf: 89 / Rg: 100
<b>SDCM</b>	SDCM2
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	18°
<b>LED TECHNICS (LIGHT SOURCE)</b>	1087lm // 9W // 121lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	776lm // 10,4W // 75lm/W

### Requirements

SPY 66 TUBE  
 LED POWER SUPPLY 500mA-DC TW

### Options

COVERSET R 90-100

### Accessories

HONEYCOMB 57  
 SPREAD LENS 57  
 LINEAR SPREAD LENS 57  
 SOFTENING LENS 57  
 GLASS SBL 57

# DELTALIGHT

## SPY 66 ON TW 96518


24624 9010 B

For detailed installation instructions, please consult the manual : [24624\\_XXX0\\_HAND.pdf](#)


### FINISH YOUR SPECIFICATION

#### LED power supplies

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**21012 0355** LED POWER SUPPLY 500mA-DC 2CH TW DIM5

2

Dimtype: DALI

Cutout dimension (mm): 85


#### Coversets



**204 00 90 ANO** COVERSET R 90 ANO

**204 00 90 B** COVERSET R 90 B

**204 00 90 W** COVERSET R 90 W



**204 00 100 ANO** COVERSET R 100 ANO

**204 00 100 B** COVERSET R 100 B

**204 00 100 W** COVERSET R 100 W


# DELTALIGHT

## SPY 66 ON TW 96518


24624 9010 B

### Light altering devices


---




**24611 0150 B** HONEYCOMB 57 SINGLE USE B




**24611 0160** GLASS SBL 57




**24611 0170** LINEAR SPREAD LENS 57



**24611 0190** SOFTENING LENS 57



**24611 0200** SPREAD LENS 57



**24611 0210 B** HONEYCOMB 57 DOUBLE USE B

### Finish your product

---



**24611 0100 B** SPY 66 TUBE B

**24611 0100 FBR** SPY 66 TUBE FBR

**24611 0100 FG** SPY 66 TUBE FG

**24611 0100 GC** SPY 66 TUBE GC

# DELTALIGHT

## SPY 66 ON TW 96518

24624 9010 B

**24611 0100 W** SPY 66 TUBE W

### Replaceable reflector / lens



**24611 0220** SPY 66 REFLECTOR 18°



**24611 0230** SPY 66 REFLECTOR 30°



**24611 0240** SPY 66 REFLECTOR 45°

Notes: