

## INLET TRIMLESS L38 927



13216 9200 B-W

AVAILABLE IN

**BLACK-WHITE** 13216 9200 B-W

**GOLD COLORED-WHITE** 13216 9200 GC-W

**WHITE-WHITE** 13216 9200 W-W



[View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Wall Recessed
<b>CUTOUT SHAPE/SIZE (MM)</b>	rectangle - KIT
<b>RECESSED DEPTH (MM)</b>	50
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.5
<b>ADJUSTABILITY</b>	non adjustable
<b>INFORMATION</b>	EXCL.LED POWER SUPPLY 24V-DC

### Electrical info

<b>ELECTRICAL</b>	24V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	depending on power supply
<b>ENERGY CLASS</b>	F

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	1 x LEDFLEX 5,6W / CRI>90 / 2700K / 654lm
<b>LED TECHNICS (LIGHT SOURCE)</b>	654lm // 5,6W // 117lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	203lm // 6,4W // 32lm/W

### Requirements

MOUNTING KIT INLET TRIMLESS L38  
LED POWER SUPPLY 24V-DC (Remote)

For detailed installation instructions, please consult the manual : [13216\\_XXX0\\_HAND.pdf](#)

# DELTALIGHT

## INLET TRIMLESS L38 927

13216 9200 B-W

### FINISH YOUR SPECIFICATION

#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**300 89 24 150** LED POWER SUPPLY 24V-DC / 150W

24

Dimtype: non-dimmable

Cutout dimension (mm): 75




**21012 0101** LED POWER SUPPLY 24V-DC / 60W IP67 DIM1

9

Dimtype: 1-10V

Cutout dimension (mm): 65




**21012 0111** LED POWER SUPPLY 24V-DC / 90W IP67 DIM1

14

Dimtype: 1-10V

Cutout dimension (mm): 75




**21012 0121** LED POWER SUPPLY 24V-DC / 120W IP67 DIM1

19

Dimtype: 1-10V

Cutout dimension (mm): 75




**21012 0135** LED POWER SUPPLY 24V-DC / 60W IP67 DIM5

9

Dimtype: DALI

Cutout dimension (mm): 65




**21012 0145** LED POWER SUPPLY 24V-DC / 90W IP67 DIM5

14

Dimtype: DALI

Cutout dimension (mm): 75




**21012 0155** LED POWER SUPPLY 24V-DC / 120W IP67 DIM5

19

Dimtype: DALI

Cutout dimension (mm): 75



**21012 0160** LED POWER SUPPLY 24V-DC / 24W

3


Dimtype: non-dimmable

Cutout dimension (mm): 55

# DELTALIGHT

## INLET TRIMLESS L38 927

13216 9200 B-W




**21012 0171** LED POWER SUPPLY 24V-DC / 60W DIM1

9



**Dimtype: 1-10V**

**Cutout dimension (mm): 61**




**21012 0181** LED POWER SUPPLY 24V-DC / 90W DIM1

14



**Dimtype: 1-10V**

**Cutout dimension (mm): 70**




**21012 0191** LED POWER SUPPLY 24V-DC / 120W DIM1

19



**Dimtype: 1-10V**

**Cutout dimension (mm): 70**




**21012 0205** LED POWER SUPPLY 24V-DC / 60W DIM5

9



**Dimtype: DALI**

**Cutout dimension (mm): 61**



**21012 0225** LED POWER SUPPLY 24V-DC / 100W DIM5


16



**Dimtype: DALI**

**Cutout dimension (mm): 70**

### Mounting kits



**13210 0060** MOUNTING KIT INLET TRIMLESS L38



**Cutout dimension (mm): 395 x 75**

Notes: