DELTALIGHT

SL19 - SPY 39 L 93020 MDL

REFERENCE 27032 9320 B

AVAILABLE IN
BLACK 27032 9320 B
FLEMISH BRONZE 27032 9320 FBR
FLEMISH GOLD 27032 9320 FG
GOLD COLOURED 27032 9320 GC
WHITE 27032 9320 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 85° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 48V-DC

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	D
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm
TM-30 VALUES	Rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	683lm // 9,9W // 69lm/W

Requirements

SPY 39 L TUBE
LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : **27032_XXX0_HAND.pdf**

DELTALIGHT

SL19 - SPY 39 L 93020 MDL

27032 9320 B

FINISH YOUR SPECIFICATION

SMART 48

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 90 011 SMART 48 MODULATOR DIM9 — 19

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD — 19

Dimtype: WDL = wireless dimmable

LED power supplies

# of Fixtures

Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 10

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 24

Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 10

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W — 20

Dimtype: non-dimmable

Cutout dimension (mm): 40

DELTALIGHT

SL19 - SPY 39 L 93020 MDL

27032 9320 B

Finish your product

	**24144 0020 B**	SPY 39 L TUBE B	☐
	24144 0020 FBR	SPY 39 L TUBE FBR	☐
	24144 0020 FG	SPY 39 L TUBE FG	☐
	24144 0020 GC	SPY 39 L TUBE GC	☐
	24144 0020 W	SPY 39 L TUBE W	☐

COMPATIBLE COMPOSABLES

SHIFTLINE 19 profile		Available Colours
	**27011 0050** SL19 - PROFILE 2m	● ○
	**27011 0060** SL19 - PROFILE 3m	● ○

Notes: