
DELTALIGHT




# D-LINER 30 INF LOC2 1114 94058 DIM5

**REFERENCE** 32085 9425 W-W

AVAILABLE IN
**BLACK-BLACK** 32085 9425 B-B
**WHITE-WHITE** 32085 9425 W-W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Ceiling Recessed |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0 |
| **ADJUSTABILITY** | non adjustable |
| **INFORMATION** | 48 x REFLECTOR FL-58°<br>INCL.DIMMABLE LED POWER SUPPLY 520mA-DC<br>INCL.1 x CABLE 5 x 0,75mm² - 0,5m + WIELAND PLUG GST18i5 male pastelblue |

| Electrical info | |
|---|---|
| **ELECTRICAL** | 220-240V / 0\|50-60Hz |
| **CLASS** | I |
| **POWER SUPPLY** | YES |
| **DIM TYPE** | DALI |
| **ENERGY CLASS** | C |
| **CERTIFICATES** | EPD |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED cluster 17,3W / CRI>90 / 4000K / 3154lm |
| **LED TECHNICS (LIGHT SOURCE)** | 3154lm // 17,3W // 183lm/W |
| **LED TECHNICS (LUMINAIRE)** | 2495lm // 20W // 125lm/W |

For detailed installation instructions, please consult the manual : **32085_XXX5_HAND.pdf**

## CEILING COMPATIBILITY

| Ceiling Type | Mounting Kit |
|---|---|
| **Acoustic climate-control ceiling Hunter Douglas 30BD** | - |

DELTALIGHT

## D-LINER 30 INF LOC2 1114 94058 DIM5

32085 9425 W-W

Notes: