



## LOGIC LINEAR ON 880 93040 DIM5

30835 9335 N

AVAILABLE IN



**ALU GREY** 30835 9335 A

**BLACK** 30835 9335 B

**FLEMISH BRONZE OUTDOOR** 30835 9335 FBRX

**ANTHRACITE** 30835 9335 N

**WHITE** 30835 9335 W



[View on website](#)



| General info                         |                                                                       |
|--------------------------------------|-----------------------------------------------------------------------|
| LOCATION                             | outdoor                                                               |
| INSTALLATION                         | Floor Surface mounted, Wall Surface mounted                           |
| INGRESS PROTECTION                   | IP67                                                                  |
| PROTECTION AGAINST MECHANICAL IMPACT | IK07                                                                  |
| WEIGHT (KG)                          | 2                                                                     |
| INFORMATION                          | 16 x LENS WFL-40°<br>EXCL.LED POWER SUPPLY 48V-DC<br>DALI DT8 dimming |
| Electrical info                      |                                                                       |
| ELECTRICAL                           | 48V-DC                                                                |
| CLASS                                | III                                                                   |
| DIM TYPE                             | DALI                                                                  |
| ENERGY CLASS                         | E                                                                     |
| CERTIFICATES                         | CB, ENEC                                                              |
| Lightsource info                     |                                                                       |
| LIGHTSOURCE NAME                     | LED                                                                   |
| LIGHTSOURCE                          | LED cluster 28,8W / CRI>90 (R9: 60) / 3000K / 3597lm                  |
| TM-30 VALUES                         | Rf: 92 / Rg: 99                                                       |
| SDCM                                 | SDCM3                                                                 |
| RISKGROUP                            | RG2                                                                   |
| LM80                                 | L80 > 150000                                                          |
| BEAMANGLE                            | 40°                                                                   |
| LED TECHNICS (LIGHT SOURCE)          | 3597lm // 28,8W // 121lm/W                                            |
| LED TECHNICS (LUMINAIRE)             | 2738lm // 33,1W // 83lm/W                                             |

### Requirements

WALL BRACKET SET  
FLOOR BRACKET SET  
IP68 CABLE + CONNECTOR 5P  
LED POWER SUPPLY 48V-DC


### Options


THROUGH WIRING SET IP68

For detailed installation instructions, please consult the manual : [30835\\_XXX5\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION

| LED power supplies                                                                                                                                                                                                                                                                                                                                                         |  | # of Fixtures             |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|---------------------------|
| <div><div></div><div># of fixtures indicates how many devices can be connected (min -&gt; max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.</div></div> |  | Min current   Max current |

|                                                                                  |                                                 |   |                      |
|----------------------------------------------------------------------------------|-------------------------------------------------|---|----------------------|
|  | <b>21032 0390</b> LED POWER SUPPLY 48V-DC / 90W | 2 | <input type="text"/> |
|                                                                                  | Dimtype: non-dimmable                           |   |                      |
|                                                                                  | Cutout dimension (mm): 75                       |   |                      |

| Fixation components                                                                |                        |                             |                      |
|------------------------------------------------------------------------------------|------------------------|-----------------------------|----------------------|
|  | <b>30810 0040</b>      | LOGIC LINEAR 880 BOX EXTEND | <input type="text"/> |
|                                                                                    |                        |                             |                      |
|                                                                                    | <b>30810 0040 INOX</b> | WALL BRACKET SET 60 INOX    | <input type="text"/> |
|                                                                                    | <b>30810 0040 N</b>    | WALL BRACKET SET 60 N       | <input type="text"/> |
|  | <b>30810 0050 INOX</b> | WALL BRACKET SET 100 INOX   | <input type="text"/> |
|                                                                                    |                        |                             |                      |
|                                                                                    | <b>30810 0050 N</b>    | WALL BRACKET SET 100 N      | <input type="text"/> |
|  | <b>30810 0060 INOX</b> | WALL BRACKET SET 200 INOX   | <input type="text"/> |
|                                                                                    |                        |                             |                      |
|                                                                                    | <b>30810 0060 N</b>    | WALL BRACKET SET 200 N      | <input type="text"/> |

# DELTALIGHT

## LOGIC LINEAR ON 880 93040 DIM5

30835 9335 N



**30810 0070 INOX** FLOOR BRACKET SET INOX

☐

### Electric connection parts



**30810 0080** IP68 CABLE + CONNECTOR 5P - 0,5m

☐

**30810 0090** IP68 CABLE + CONNECTOR 5P - 2m

☐

**30810 0110** THROUGH WIRING SET IP68 880

☐

Notes: