
DELTALIGHT




LOGIC LINEAR 880 HONEYCOMB 92725 DIM5

REFERENCE 30821 9225 INOX

AVAILABLE IN
INOX 30821 9225 INOX





View on website

General info	
LOCATION	outdoor
INSTALLATION	Floor Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - BOX
RECESSED DEPTH (MM)	140
INGRESS PROTECTION	IP67
PROTECTION AGAINST MECHANICAL IMPACT	IK09
WEIGHT (KG)	4.4
ADJUSTABILITY	non adjustable
INFORMATION	16 x LENS FL-25° INCL.HONEYCOMB INCL.DIMMABLE LED POWER SUPPLY 650mA-DC INCL.1 x CABLE H07 RN-F 5 x 1mm² 0,5m INCL.IP68 CONNECTOR 5P ESG 8mm max.500kg

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 28,8W / CRI>90 (R9: 50) / 2700K / 3288lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	25°
LED TECHNICS (LIGHT SOURCE)	3288lm // 28,8W // 111lm/W
LED TECHNICS (LUMINAIRE)	1332lm // 33,1W // 40lm/W

Requirements

LOGIC LINEAR BOX

DELTALIGHT


LOGIC LINEAR 880 HONEYCOMB 92725 DIM5

30821 9225 INOX

For detailed installation instructions, please consult the manual : **30821_XXX5_HAND.pdf**

FINISH YOUR SPECIFICATION


Ground mounting boxes



30810 0030 LOGIC LINEAR 880 BOX ☐

Cutout dimension (mm): 920 x 150

Waterproof connection parts



21034 0150 IP68 Y-CONNECTOR 5P ☐

Notes: