
DELTALIGHT




DOT.COM L2 ON 92732 DIM8

REFERENCE 424 113 02 922 ED8 B-B

AVAILABLE IN
BLACK-BLACK 424 113 02 922 ED8 B-B
WHITE-BLACK 424 113 02 922 ED8 W-B





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.7
ADJUSTABILITY	non adjustable
INFORMATION	2 x REFLECTOR FL-32° INCL.DIMMABLE LED POWER SUPPLY 700mA-DC

Electrical info	
ELECTRICAL	230V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 4,1W / CRI>90 (R9: 50) / 2700K / 425lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
BEAMANGLE	32°
LED TECHNICS (LIGHT SOURCE)	425lm // 4,1W // 104lm/W
LED TECHNICS (LUMINAIRE)	286lm // 4,7W // 61lm/W

For detailed installation instructions, please consult the manual : **424_113_02_XXX_HAND.pdf**

Notes:

DOT.COM L2 ON 92732 DIM8

424 113 02 922 ED8 B-B