



ENTERO RD-M TRIMLESS 92710



28429 9210 B

AVAILABLE IN

BLACK 28429 9210 B

FULL WHITE 28429 9210 FW

GOLD COLOURED 28429 9210 GC



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	135
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.43
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	LENS SP-10° EXCL.LED POWER SUPPLY 350-700mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 3,9-8,2W / CRI>90 (R9: 56) / 2700K / 385-677lm
TM-30 VALUES	rf: 91 / Rg: 99
SDCM	SDCM2
RISKGROUP	RG2 (threshold 0,6m)
LM80	L90B10 > 41000
BEAMANGLE	10°
LED TECHNICS (LIGHT SOURCE)	677lm // 8,2W // 83lm/W
LED TECHNICS (LUMINAIRE)	610lm // 9,4W // 65lm/W

Requirements

MOUNTING KIT ENTERO ROUND M

LED POWER SUPPLY 350 / 500 / 700mA-DC DIM (Remote)

Accessories

ENTERO M HONEYCOMB

For detailed installation instructions, please consult the manual : [28429_XXX0_HAND.pdf](#)

ENTERO RD-M TRIMLESS 92710


28429 9210 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Plasterboard	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Stucanet	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Concrete + plaster	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Lintel + plaster	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Hollow-core slab + plaster	 28400 0020 - MOUNTING KIT ENTERO RD-M O.F.A.	Required
 Stretched ceiling	 28400 0080 - MOUNTING KIT ENTERO RD-M CSC	Required
	 28400 0140 - MOUNTING KIT ENTERO RD-M WSC	Required


FINISH YOUR SPECIFICATION

Emergency units

	21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B	☐
	21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W	☐







LED power supplies

of Fixtures

300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1		Min current Max current
Dimtype: 1-10V		
Cutout dimension (mm): 30		
		3 ☐











ENTERO RD-M TRIMLESS 92710

28429 9210 B

	300 48 350 ED5 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 45	3	☐
	300 48 350 MDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL Dimtype: non-dimmable Cutout dimension (mm): 30	3	☐
	300 48 350 WDL LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 45	3	☐
	300 48 500 ED1 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM1 Dimtype: 1-10V Cutout dimension (mm): 30	3	☐
	300 48 500 ED5 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5 Dimtype: DALI Cutout dimension (mm): 45	3	☐
	300 48 500 MDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W MDL Dimtype: non-dimmable Cutout dimension (mm): 30	3	☐
	300 48 500 WDL LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 45	3	☐
	300 48 700 ED1 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM1 Dimtype: 1-10V Cutout dimension (mm): 30	3	☐
	300 48 700 ED5 LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5 Dimtype: DALI Cutout dimension (mm): 45	3	☐
	300 48 700 MDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W MDL Dimtype: non-dimmable Cutout dimension (mm): 30	3	☐











ENTERO RD-M TRIMLESS 92710

28429 9210 B

	300 48 700 WDL LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 45	3	☐
	300 90 61 LED POWER SUPPLY MULTI-POWER DIM6 Dimtype: mains (phase cut-off) or push button Cutout dimension (mm): 56	3 3 3	☐
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 82	6(6) 6(6) 6(4)	☐
	300 90 64 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 72	2->4(3) 4(2) 3(1)	☐
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 Dimtype: 1-10V or DALI or push button	3 3	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5 Dimtype: DALI Cutout dimension (mm): 72	4(3) 4(2) 3(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9 Dimtype: 1-10V or DALI or push button Cutout dimension (mm): 84	2->9(10) 9(6) 7(4)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7 Dimtype: 1-10V or push button Cutout dimension (mm): 55	2->4(3) 3(2) 2(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	4(3) 3(2) 2(1)	☐
	300 90 135 LED POWER SUPPLY MULTI-POWER HV Dimtype: non-dimmable Cutout dimension (mm): 90	5->7 4->7 4->6 3->6	☐

ENTERO RD-M TRIMLESS 92710





28429 9210 B

	21012 0010 LED POWER SUPPLY MULTI POWER Dimtype: non-dimmable Cutout dimension (mm): 50	2->3 3 3	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1-10V Cutout dimension (mm): 54	4 4 4	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	4 4 4	☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 84	6(6) 5(5) 5(4)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = wireless dimmable Cutout dimension (mm): 54	4 4 4	☐
	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 50	2->2	☐
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 50	3->3	☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 55	2->2 2->2	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 55	3->4 3->4	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: mains (phase cut-off) Cutout dimension (mm): 48	3 3 2	☐


DELTALIGHT

ENTERO RD-M TRIMLESS 92710


28429 9210 B

	<u>21012 0480</u> LED POWER SUPPLY 350mA-DC / 17W IP68	4(3)	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 60		
	<u>21012 0490</u> LED POWER SUPPLY 700mA-DC / 30W IP68	3(1)	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 60		
	<u>21012 0500</u> LED POWER SUPPLY 500mA-DC / 24W IP68	4(2)	☐
	Dimtype: non-dimmable		
	Cutout dimension (mm): 60		
	<u>21032 0295</u> LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	3	☐
	Dimtype: DALI		
	Cutout dimension (mm): 30		
	<u>21032 0305</u> LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	3	☐
	Dimtype: DALI		
	Cutout dimension (mm): 30		
	<u>21032 0315</u> LED POWER CONVERTER 48V-DC to 700 mA-DC / 25W DIM5	3	☐
	Dimtype: DALI		
	Cutout dimension (mm): 30		

Mounting kits

	<u>28400 0020</u> MOUNTING KIT ENTERO RD-M O.F.A.	☐
	Cutout dimension (mm): 127	

Mounting kits stretched ceiling

	<u>28400 0080</u> MOUNTING KIT ENTERO RD-M CSC	☐
--	---	--------------------------

DELTALIGHT

ENTERO RD-M TRIMLESS 92710


28429 9210 B



28400 0140 MOUNTING KIT ENTERO RD-M WSC



Light altering devices



28500 0110 B ENTERO M HONEYCOMB SINGLE USE B



Notes: