



OML50 - PRISMATIC LENS DU HO 656mm 930

31632 9300 B

BESCHIKBAAR IN
ZWART 31632 9300 B



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	1
INFO	INCLLED POWER SUPPLY CABLING 1 CIRCUIT

Elektrische info

ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	niet dimbaar
ENERGIE KLASSE	D
CERTIFICATES	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 15,5W / CRI>90 (R9: 50) / 3000K / 2380lm UP: LED cluster 12,1W / CRI>90 (R9: 50) / 3000K / 1747lm
TM-30 WAARDEN	Rf: 92 / Rg: 100
SMDC	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 2380lm // 15,5W // 153lm/W UP: 1747lm // 12,1W // 145lm/W

Notes: