





FRAX MB SUPERSPOT 92708 HONEYCOMB DIM5

26110 9225 PGR

AVAILABLE IN
FLEMISH BRONZE OUTDOOR 26110 9225 FBRX
ANTHRACITE 26110 9225 N
PINE GREEN 26110 9225 PGR



[View on website](#)



General info	
LOCATION	outdoor
INSTALLATION	Floor Surface mounted, Wall Surface mounted
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	2.1
ADJUSTABILITY	0° to 120° swiveling, 360° rotatable
INFORMATION	7 x LENS SP-8° INCL.DIMMABLE LED POWER SUPPLY 900mA-DC INCL.HONEYCOMB INCL.1 x CABLE H05 RN-F 5 x 1mm ² 2m
Electrical info	
ELECTRICAL	110-277V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	F
CERTIFICATES	EPD, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 18,2W / CRI>90 (R9: 50) / 2700K / 1884lm
TM-30 VALUES	Rf: 91 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	8°
LED TECHNICS (LIGHT SOURCE)	1884lm // 18,2W // 103lm/W
LED TECHNICS (LUMINAIRE)	1432lm // 20,9W // 68lm/W

Requirements

FRAX BRACKET
FRAX PIN
FRAX STRAP

Options

FRAX ANTI VANDAL SCREWS

Accessories

FRAX M KAP


FRAX MB SUPERSPOT 92708 HONEYCOMB DIM5

26110 9225 PGR


For detailed installation instructions, please consult the manual : [26110_XX25_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Pins and plates for bollards

	26070 0040 FBRX FRAX PIN FBRX	☐
	26070 0040 N FRAX PIN N	☐
	26070 0040 PGR FRAX PIN PGR	☐

Fixation components

	26070 0060 FBRX FRAX BRACKET FBRX	☐
	26070 0060 N FRAX BRACKET N	☐
	26070 0060 PGR FRAX BRACKET PGR	☐

Light altering devices


	26070 0020 N FRAX M KAP N	☐
--	----------------------------------	--------------------------

DELTALIGHT


FRAX MB SUPERSPOT 92708 HONEYCOMB DIM5

26110 9225 PGR

Other



26070 0030 FRAX ANTI VANDAL SCREWS 5 PCS

☐

26070 0050 N FRAX STRAP N

☐

Notes: