



## LOGIC LINEAR ON 880 93040 DIM5

30835 9335 W

AVAILABLE IN


**ALU GREY** 30835 9335 A

**BLACK** 30835 9335 B

**FLEMISH BRONZE OUTDOOR** 30835 9335 FBRX

**ANTHRACITE** 30835 9335 N

**WHITE** 30835 9335 W



[View on website](#)



| General info                         |                                                                       |
|--------------------------------------|-----------------------------------------------------------------------|
| LOCATION                             | outdoor                                                               |
| INSTALLATION                         | Floor Surface mounted, Wall Surface mounted                           |
| INGRESS PROTECTION                   | IP67                                                                  |
| PROTECTION AGAINST MECHANICAL IMPACT | IK07                                                                  |
| WEIGHT (KG)                          | 2                                                                     |
| INFORMATION                          | 16 x LENS WFL-40°<br>EXCL.LED POWER SUPPLY 48V-DC<br>DALI DT8 dimming |
| Electrical info                      |                                                                       |
| ELECTRICAL                           | 48V-DC                                                                |
| CLASS                                | III                                                                   |
| DIM TYPE                             | DALI                                                                  |
| ENERGY CLASS                         | E                                                                     |
| CERTIFICATES                         | CB, ENEC                                                              |
| Lightsource info                     |                                                                       |
| LIGHTSOURCE NAME                     | LED                                                                   |
| LIGHTSOURCE                          | LED cluster 28,8W / CRI>90 (R9: 60) / 3000K / 3597lm                  |
| TM-30 VALUES                         | Rf: 92 / Rg: 99                                                       |
| SDCM                                 | SDCM3                                                                 |
| RISKGROUP                            | RG2                                                                   |
| LM80                                 | L80 > 150000                                                          |
| BEAMANGLE                            | 40°                                                                   |
| LED TECHNICS (LIGHT SOURCE)          | 3597lm // 28,8W // 121lm/W                                            |
| LED TECHNICS (LUMINAIRE)             | 2738lm // 33,1W // 83lm/W                                             |

### Requirements

WALL BRACKET SET  
FLOOR BRACKET SET  
IP68 CABLE + CONNECTOR 5P  
LED POWER SUPPLY 48V-DC

### Options

THROUGH WIRING SET IP68

## LOGIC LINEAR ON 880 93040 DIM5

30835 9335 W

For detailed installation instructions, please consult the manual : [30835\\_XXX5\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION


#### LED power supplies

#### # of Fixtures



# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**21032 0390** LED POWER SUPPLY 48V-DC / 90W

Dimtype: non-dimmable

Cutout dimension (mm): 75

2

#### Fixation components



**30810 0040** LOGIC LINEAR 880 BOX EXTEND

**30810 0040 INOX** WALL BRACKET SET 60 INOX

**30810 0040 N** WALL BRACKET SET 60 N



**30810 0050 INOX** WALL BRACKET SET 100 INOX

**30810 0050 N** WALL BRACKET SET 100 N



**30810 0060 INOX** WALL BRACKET SET 200 INOX

**30810 0060 N** WALL BRACKET SET 200 N

# DELTALIGHT

## LOGIC LINEAR ON 880 93040 DIM5

30835 9335 W



**30810 0070 INOX** FLOOR BRACKET SET INOX

☐

### Electric connection parts



**30810 0080** IP68 CABLE + CONNECTOR 5P - 0,5m

☐

**30810 0090** IP68 CABLE + CONNECTOR 5P - 2m

☐

**30810 0110** THROUGH WIRING SET IP68 880

☐

Notes: