




FRAX MB POLE SUPERSPOT 93008
HONEYCOMB

26026 9310 N

AVAILABLE IN
ANTHRACITE 26026 9310 N



 [View on website](#)



General info	
LOCATION	outdoor
INSTALLATION	Pole Pole top
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK08
WEIGHT (KG)	2.3
ADJUSTABILITY	0° to 120° swiveling, 360° rotatable
INFORMATION	7 x LENS SP-8° INCL.LED POWER SUPPLY 900mA-DC INCL.HONEYCOMB INCL.1 x CABLE H05 RN-F 3 x 1mm² 6m

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 18,2W / CRI>90 (R9: 60) / 3000K / 2064lm
TM-30 VALUES	Rf: 92 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 150000
BEAMANGLE	8°
LED TECHNICS (LIGHT SOURCE)	2064lm // 18,2W // 113lm/W
LED TECHNICS (LUMINAIRE)	1569lm // 20,9W // 75lm/W

Requirements
FRAX BRACKET


Options
FRAX ANTI VANDAL SCREWS

Accessories
FRAX M KAP

For detailed installation instructions, please consult the manual : [26026_XXX0_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Light altering devices




26070 0020 N FRAX M KAP N

☐


Other



26070 0030 FRAX ANTI VANDAL SCREWS 5 PCS

☐

26071 0050 N FRAX POLE 60 BRACKET N

☐

26071 0060 N FRAX POLE 80 BRACKET N

☐

Notes: