



SPY 39 CLIP WALLWASH SOFT 930

24153 9000 B-B

AVAILABLE IN

NOIR-NOIR 24153 9000 B-B

ALU BROSSÉ-NOIR 24153 9000 BRA-B

ANTHRACITE BROSSÉ-NOIR 24153 9000 BRAT-B

CUIVRE BROSSÉ-NOIR 24153 9000 BRCU-B

OR BROSSÉ-NOIR 24153 9000 BRG-B

BRONZE VIEUX BROSSÉ-NOIR 24153 9000 BROB-B



FLEMISH BRONZE-NOIR 24153 9000 FBR-B

FLEMISH GOLD-NOIR 24153 9000 FG-B

ENTIÈREMENT BLANC 24153 9000 FW

COULEUR OR-NOIR 24153 9000 GC-B

BLANC-BLANC 24153 9000 W-W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Semi-encasté
CUTOUT SHAPE/SIZE (MM)	circulaire - 43
RECESSED DEPTH (MM)	40
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° à 85° inclinable, 355° rotatif
INFORMATION	WALLWASH LENS EXCL.DIMMABLE LED POWER SUPPLY 350mA-DC

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	F
CERTIFICATION	LCA

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6W / CRI>90 (R9: 50) / 3000K-1800K / 623lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	623lm // 6W // 105lm/W
LED TECHNICS (LUMINAIRE)	341lm // 6,9W // 49lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

SPY 39 CLIP WALLWASH SOFT 930

24153 9000 B-B


For detailed installation instructions, please consult the manual : [24153_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Wood	-
 Concrete	-
 Hollow-core slab	-
 Stretched ceiling	-

FINISH YOUR SPECIFICATION

les batteries de secours


	21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B	☐
	21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W	☐

les alimentations led

		# of Fixtures
 web2print_power_supply_info_box		Min current Max current
	300 48 350 ED1 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 30	2 ☐

SPY 39 CLIP WALLWASH SOFT 930

24153 9000 B-B



300 48 350 ED5


LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

2



Dimtype: DALI

Cutout dimension (mm): 45



300 48 350 MDL


LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W MDL

2



Dimtype: non dimmable

Cutout dimension (mm): 30



300 48 350 WDL


LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W WDL

2



Dimtype: WDL = dimmable sans fil

Cutout dimension (mm): 45



300 90 61


LED POWER SUPPLY MULTI-POWER DIM6

2



Dimtype: fin de phase ou bouton poussoir

Cutout dimension (mm): 56



300 90 63


LED POWER SUPPLY MULTI-POWER DIM9

4(4)



Dimtype: 1 à 10 V ou DALI ou bouton poussoir

Cutout dimension (mm): 82



300 90 64


LED POWER SUPPLY MULTI-POWER DIM7

3(2)



Dimtype: 1 à 10 V ou bouton poussoir

Cutout dimension (mm): 72




300 90 67

LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9

2



Dimtype: 1 à 10 V ou DALI ou bouton poussoir



300 90 68


LED POWER SUPPLY MULTI-POWER DIM5

2(2)



Dimtype: DALI

Cutout dimension (mm): 72



300 90 69


LED POWER SUPPLY MULTI-POWER HV DIM9

2->6(6)



Dimtype: 1 à 10 V ou DALI ou bouton poussoir

Cutout dimension (mm): 84



300 90 124

LED POWER SUPPLY MULTI-POWER DIM7

2(2)











Dimtype: 1 à 10 V ou bouton poussoir

Cutout dimension (mm): 55

SPY 39 CLIP WALLWASH SOFT 930

24153 9000 B-B

	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5 Dimtype: DALI Cutout dimension (mm): 55	2(2) ☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1 Dimtype: 1 à 10 V Cutout dimension (mm): 54	3 ☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5 Dimtype: DALI Cutout dimension (mm): 54	3 ☐
	21012 004W LED POWER SUPPLY MULTI-POWER WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 84	4(4) ☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL Dimtype: WDL = dimmable sans fil Cutout dimension (mm): 54	3 ☐
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8 Dimtype: fin de phase Cutout dimension (mm): 50	2->2 ☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8 Dimtype: fin de phase Cutout dimension (mm): 48	2 ☐
	21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8 Dimtype: fin de phase Cutout dimension (mm): 40	1 ☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5 Dimtype: DALI Cutout dimension (mm): 30	2 ☐

DELTALIGHT

SPY 39 CLIP WALLWASH SOFT 930

24153 9000 B-B

Notes: