


27328 9305 W

Technical drawing of a mechanical part, likely a bracket or support. The drawing shows a cylindrical component with a diameter of $\varnothing 39$ and a length of 92. A rectangular plate with a width of 160 and a height of 7 is attached to the side of the cylinder. The plate has a thickness of 20. A dimension of 11 is indicated for the distance from the centerline of the cylinder to the inner edge of the plate. A rotation symbol indicates a range of motion from 0° to 35° .



[View on website](#)





LED POWER SUPPLY 48V-DC

Delta Light NV may revise the information and technical data at any time without notice. Version: 29/04/2026



SPL14 - SPY 39 FOCUS 930 DIM5

27328 9305 W

FINISH YOUR SPECIFICATION

LED power supplies		# of Fixtures
 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the ' ' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.		Min current Max current
 300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN Dimtype: non-dimmable		10
 300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN Dimtype: non-dimmable		24
 21012 0230 LED POWER SUPPLY 48V-DC / 100W Dimtype: non-dimmable Cutout dimension (mm): 40		10
 21012 0240 LED POWER SUPPLY 48V-DC / 200W Dimtype: non-dimmable Cutout dimension (mm): 40		20

COMPATIBLE COMPOSABLES

SPLITLINE 14 profile	Available Colours
 27300 0020 SPL14 - PROFILE 2m	
 27300 0030 SPL14 - PROFILE 3m	

Notes:

DELTALIGHT

SPL14 - SPY 39 FOCUS 930 DIM5

27328 9305 W