



## BOXY XL R 92720 DIM1



251 71 21 921 ED1 B-B

AVAILABLE IN

**BLACK-BLACK** 251 71 21 921 ED1 B-B

**WHITE-BLACK** 251 71 21 921 ED1 W-B

**WHITE-WHITE** 251 71 21 921 ED1 W-W



[View on website](#)



### General info

|                           |                                                             |
|---------------------------|-------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                      |
| <b>INSTALLATION</b>       | Ceiling Surface mounted                                     |
| <b>INGRESS PROTECTION</b> | IP20                                                        |
| <b>WEIGHT (KG)</b>        | 1.5                                                         |
| <b>ADJUSTABILITY</b>      | non adjustable                                              |
| <b>INFORMATION</b>        | REFLECTOR FL-20°<br>INCL.DIMMABLE LED POWER SUPPLY 700mA-DC |

### Electrical info

|                     |                    |
|---------------------|--------------------|
| <b>ELECTRICAL</b>   | 120-240V / 50-60Hz |
| <b>CLASS</b>        | II                 |
| <b>POWER SUPPLY</b> | YES                |
| <b>DIM TYPE</b>     | 1-10V              |
| <b>ENERGY CLASS</b> | D                  |
| <b>CERTIFICATES</b> | CB, ENEC, LCA, RCM |

### Lightsource info

|                                    |                                                    |
|------------------------------------|----------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                |
| <b>LIGHTSOURCE</b>                 | LED array 23,2W / CRI>90 (R9: 60) / 2700K / 3031lm |
| <b>TM-30 VALUES</b>                | rf: 89 / Rg: 100                                   |
| <b>SDCM</b>                        | SDCM1                                              |
| <b>RISKGROUP</b>                   | RG1                                                |
| <b>LM80</b>                        | L90B10 > 50000                                     |
| <b>BEAMANGLE</b>                   | 20°                                                |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 3031lm // 23,2W // 130lm/W                         |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 2636lm // 26,7W // 99lm/W                          |

### Accessories

HONEYCOMB 78  
SOFTENING LENS 78  
GLASS SBL 78


For detailed installation instructions, please consult the manual : [251\\_71\\_21\\_XXX\\_ED1\\_HAND.pdf](#)

BOXY XL R 92720 DIM1

251 71 21 921 ED1 B-B

FINISH YOUR SPECIFICATION

Miscellaneous control equipment




**300 90 016 ED1** WIRELESS CONTROL 5A DIM1

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 86

☐

Light altering devices



**201 02 01 B** HONEYCOMB 78 B

☐

**201 02 04** SOFTENING LENS 78

☐

**201 02 05** GLASS SBL 78

☐

Notes: