
DELTALIGHT




INFORM SQ P200-4 DOWN 93067

REFERENCE 25515 9320 W-B

AVAILABLE IN
BLACK-BLACK 25515 9320 B-B
BLACK-FLEMISH GOLD 25515 9320 B-FG
WHITE-BLACK 25515 9320 W-B
WHITE-WHITE 25515 9320 W-W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.4
ADJUSTABILITY	non adjustable
INFORMATION	48 x REFLECTOR FL-67° EXCL.LED POWER SUPPLY 400/600mA-DC INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m POWER VIA CABLE SUSPENSION

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, EPD

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	2 x (LED cluster 7-11,2W / CRI>90 (R9: 50) / 3000K / 1068-1543lm)
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	67°
LED TECHNICS (LIGHT SOURCE)	3086lm // 22,4W // 138lm/W
LED TECHNICS (LUMINAIRE)	2694lm // 25,8W // 105lm/W

Requirements

INFORM SQ POWERBOX 50W (DIM5)
INFORM POWER SUPPLY 25W + SUSPENSION+CONNECTION ST

For detailed installation instructions, please consult the manual : **25515_XXX0_HAND.pdf**



DELTALIGHT

INFORM SQ P200-4 DOWN 93067



25515 9320 W-B

FINISH YOUR SPECIFICATION

Power box

		# of Fixtures
	# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current | Max current
	**25510 0010 B** INFORM SQ POWERBOX 50W B **Dimtype: non-dimmable**	1 ☐
	25510 0010 W INFORM SQ POWERBOX 50W W	1 ☐
	**25510 0015 B** INFORM SQ POWERBOX 50W DIM5 B **Dimtype: DALI**	1 ☐
	25510 0015 W INFORM SQ POWERBOX 50W DIM5 W	1 ☐

LED power supplies

		# of Fixtures
	# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current | Max current
	**25510 0395** INFORM POWER SUPPLY 25W DIM5 **Dimtype: DALI**	1 ☐
	**25510 0440** INFORM POWER SUPPLY 25W **Dimtype: non-dimmable**	1 ☐


Electric connection parts

		# of Fixtures
	# of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.	Min current | Max current

DELTALIGHT

INFORM SQ P200-4 DOWN 93067

25515 9320 W-B



15225 0350 B SUSPENSION + CONNECTION ST B — 2 needed

Cutout dimension (mm): 27

15225 0350 W SUSPENSION + CONNECTION ST W — 2 needed

Notes: