



DEEP RINGO DYNAMIC FOCUS TRIMLESS 927

32112 9200 BRAT

AVAILABLE IN

NOIR 32112 9200 B

ALU BROSSÉ 32112 9200 BRA

ANTHRACITE BROSSÉ 32112 9200 BRAT

BRONZE BRUN BROSSÉ 32112 9200 BRBB

CUIVRE BROSSÉ 32112 9200 BRCU

OR BROSSÉ 32112 9200 BRG

BRONZE VIEUX BROSSÉ 32112 9200 BROB

CRÈME 32112 9200 CR

NOIR PIANO 32112 9200 PB

BLANC 32112 9200 W



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - Ø KIT
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	non réglable

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	G

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	13° (central part only): LED array 5,8W / CRI>90 (R9: 56) / 2700K / 528lm Or 24° central part: LED array 1W / CRI>90 (R9: 56) / 2700K / 63lm 24° ring part: LED cluster 5,5W / CRI>90 (R9: 50) / 2700K / 868lm
RVALUES	13° (central part only): rf: 91 / Rg: 99 24° central part: rf: 91 / Rg: 99 24° ring part: rf: 93 / Rg: 100
SDMC	SDCM2 SDCM3
RISKGROUP	RG2 (threshold 0,6m) RG1
LM80	L90B10 > 41000 L80 > 60000
BEAMANGLE	13°-24°
LED TECHNICS (LIGHT SOURCE)	13° (central part only): 528lm // 5,8W // 94lm/W Or 24° central part: 63lm // 1W // 100lm/W 24° ring part: 868lm // 5,5W // 158lm/W
LED TECHNICS (LUMINAIRE)	13° (central part only): 475lm // 6,7W // 71lm/W Or 24° ring part: 347lm // 6,3W // 55lm/W

DEEP RINGO DYNAMIC FOCUS TRIMLESS 927

32112 9200 BRAT

Requirements

MOUNTING KIT R82 TRIMLESS O.F.A.
LED POWER SUPPLY DYNAMIC FOCUS

For detailed installation instructions, please consult the manual : [32112_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit	
 System ceiling	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Plasterboard	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Stucanet	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Concrete + plaster	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Lintel + plaster	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Hollow-core slab + plaster	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Ventilation in plasterboard	 29810 0100 - MOUNTING KIT SIDE AIR ONLY 1	Required
	 29810 0050 - MOUNTING KIT NO AIR 101	Required
	 29810 0010 - MOUNTING KIT SIDE AIR 101	Required
 Ventilation in concrete + plaster	 29810 0210 - MOUNTING KIT TOP AIR 101	Required
	 29810 0050 - MOUNTING KIT NO AIR 101	Required
	 29810 0200 - MOUNTING KIT TOP AIR ONLY 1	Required
 Cold stretched ceiling	 15212 0070 - MOUNTING KIT R82 TRIMLESS CSC	Required
 Warm stretched ceiling	 15212 0150 - MOUNTING KIT R82 TRIMLESS WSC	Required


DEEP RINGO DYNAMIC FOCUS TRIMLESS 927


32112 9200 BRAT

FINISH YOUR SPECIFICATION

les alimentations led		# of Fixtures
 web2print_power_supply_info_box		Min current Max current

	32110 0015	LED POWER SUPPLY DYNAMIC FOCUS DIM5	3	☐
	Dimtype: DALI			
	Cutout dimension (mm): 75			
	32110 0020	LED POWER SUPPLY DYNAMIC FOCUS + WIRELESS CONTROL DIM5	3	☐
	Dimtype: DALI			
	Cutout dimension (mm): 75			

kit de montage		
	15212 2000	MOUNTING KIT R82 TRIMLESS O.F.A.
	Cutout dimension (mm): 105	

kit de montage plafond tendu		
	15212 0070 MOUNTING KIT R82 TRIMLESS CSC	☐
	15212 0150 MOUNTING KIT R82 TRIMLESS WSC	☐

Notes: