



ENTERO RD-L TRIMLESS 93018



28435 9310 GC

AVAILABLE IN

NOIR 28435 9310 B

ENTIÈREMENT BLANC 28435 9310 FW

COULEUR OR 28435 9310 GC



[View on website](#)



General info

LOCATION	interieur
INSTALLATION	Plafond Encastré
CUTOUT SHAPE/SIZE (MM)	circulaire - Ø KIT
RECESSED DEPTH (MM)	165
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.67
ADJUSTABILITY	0° à 30° inclinable, 355° rotatif
INFORMATION	REFLECTOR SP-18° EXCLLED POWER SUPPLY 350-1050mA-DC Optional REFLECTORS 30° & 45° available

Electrical info

CLASS	III
DIM TYPE	selon le type d'alimentation externe
ENERGY CLASS	D
CERTIFICATION	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 11,3-36,5W / CRI>90 (R9: 52) / 3000K / 1632-4579lm
RVALUES	rf: 90 / Rg: 99
SDMC	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	18°
LED TECHNICS (LIGHT SOURCE)	4579lm // 36,5W // 126lm/W
LED TECHNICS (LUMINAIRE)	3610lm // 42W // 86lm/W

Remarks

Max.900mA when using 1 accessory; max 800mA when using 2 accessories

Requirements

MOUNTING KIT ENTERO ROUND L

LED POWER SUPPLY 350 / 500 / 700 / 1050mA-DC DIM (Remote)

Accessories

ENTERO L HONEYCOMB

ENTERO L LINEAR SPREAD LENS

ENTERO L SPREAD LENS

ENTERO L SOFTENING LENS

ENTERO L GLASS SBL

ENTERO RD-L TRIMLESS 93018



28435 9310 GC

For detailed installation instructions, please consult the manual : [28435_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY











Ceiling Type	Mounting Kit	
 System ceiling	 28400 0030 - MOUNTING KIT ENTERO RD-L	Required
 Plasterboard	 28400 0030 - MOUNTING KIT ENTERO RD-L	Required
 Stucanet	 28400 0030 - MOUNTING KIT ENTERO RD-L	Required
 Concrete + plaster	 28400 0030 - MOUNTING KIT ENTERO RD-L	Required
 Lintel + plaster	 28400 0030 - MOUNTING KIT ENTERO RD-L	Required
 Hollow-core slab + plaster	 28400 0030 - MOUNTING KIT ENTERO RD-L	Required
 Stretched ceiling	 28400 0090 - MOUNTING KIT ENTERO RD-L CSC	Required
	 28400 0150 - MOUNTING KIT ENTERO RD-L WSC	Required

FINISH YOUR SPECIFICATION

les alimentations led		# of Fixtures
 web2print_power_supply_info_box		Min current Max current
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9 Dimtype: 1 à 10 V ou DALI ou bouton poussoir Cutout dimension (mm): 82	2(2) 2(2) 2(1) - ☐
	300 90 67 LED POWER CONVERTER 24V-DC TO MULTI CURRENT 48W DIM9 Dimtype: 1 à 10 V ou DALI ou bouton poussoir	1 ☐

ENTERO RD-L TRIMLESS 93018

28435 9310 GC


	<u>300 90 135</u> LED POWER SUPPLY MULTI-POWER HV	1 ☐
Dimtype: non dimmable	Cutout dimension (mm): 90	
	<u>300 90 136</u> LED POWER SUPPLY MULTI-POWER HC DIM9	1(1) ☐
Dimtype: 1 à 10 V ou DALI ou bouton poussoir	Cutout dimension (mm): 90	
	<u>21012 0010</u> LED POWER SUPPLY MULTI POWER	1 ☐
Dimtype: non dimmable	Cutout dimension (mm): 50	
	<u>21012 0021</u> LED POWER SUPPLY MULTI POWER DIM1	1 ☐
Dimtype: 1 à 10 V	Cutout dimension (mm): 54	
	<u>21012 0035</u> LED POWER SUPPLY MULTI POWER DIM5	1 ☐
Dimtype: DALI	Cutout dimension (mm): 54	
	<u>21012 004W</u> LED POWER SUPPLY MULTI-POWER WDL	1(1) ☐
Dimtype: WDL = dimmable sans fil	Cutout dimension (mm): 84	
	<u>21012 005W</u> LED POWER SUPPLY MULTI-POWER COMPACT WDL	1 ☐
Dimtype: WDL = dimmable sans fil	Cutout dimension (mm): 54	
	<u>21012 0480</u> LED POWER SUPPLY 350mA-DC / 17W IP68	1(1) ☐
Dimtype: non dimmable	Cutout dimension (mm): 60	
	<u>21012 0490</u> LED POWER SUPPLY 700mA-DC / 30W IP68	1(0) ☐
Dimtype: non dimmable	Cutout dimension (mm): 60	
	<u>21012 0500</u> LED POWER SUPPLY 500mA-DC / 24W IP68	1(0) ☐
Dimtype: non dimmable	Cutout dimension (mm): 60	

DELTALIGHT

ENTERO RD-L TRIMLESS 93018

28435 9310 GC

kit de montage




28400 0030 MOUNTING KIT ENTERO RD-L

Cutout dimension (mm): 162

☐

kit de montage plafond tendu



28400 0090 MOUNTING KIT ENTERO RD-L CSC

☐



28400 0150 MOUNTING KIT ENTERO RD-L WSC


☐

modifier les dispositifs de lumière




28500 0130 ENTERO L LINEAR SPREAD LENS

☐




28500 0140 ENTERO L SPREAD LENS

☐




28500 0150 ENTERO L SOFTENING LENS

☐



28500 0160 ENTERO L GLASS SBL

☐




28500 0170 B ENTERO L HONEYCOMB SINGLE USE B

☐

ENTERO RD-L TRIMLESS 93018

28435 9310 GC



28500 0180 B ENTERO L HONEYCOMB DOUBLE USE B



Notes: