
DELTALIGHT




# COMPO S HP TW 96520

**REFERENCE** 9 15721 9020 B

AVAILABLE IN
**BLACK** 9 15721 9020 B
**CHROMED** 9 15721 9020 C
**DARK CHROMED** 9 15721 9020 DC
**WHITE** 9 15721 9020 W




View on website

| General info | |
|---|---|
| **LOCATION** | indoor |
| **INSTALLATION** | Ceiling Recessed |
| **CUTOUT SHAPE/SIZE (MM)** | round - 120 |
| **RECESSED DEPTH (MM)** | 114 |
| **THICKNESS OF MOUNTING SURFACE (MM)** | max.25 |
| **INGRESS PROTECTION** | IP20 |
| **WEIGHT (KG)** | 0.18 |
| **ADJUSTABILITY** | 0° to 30° swiveling, 355° rotatable |

| Electrical info | |
|---|---|
| **CLASS** | III |
| **DIM TYPE** | depending on power supply |
| **ENERGY CLASS** | F |

| Lightsource info | |
|---|---|
| **LIGHTSOURCE NAME** | LED |
| **LIGHTSOURCE** | LED array 7,4W / CRI>90 / 2700K-6500K / 760lm |
| **SDCM** | SDCM2 |
| **RISKGROUP** | RG1 |
| **LM80** | L90B10 > 56000 |
| **BEAMANGLE** | 20° |
| **LED TECHNICS (LIGHT SOURCE)** | 760lm // 7,4W // 90lm/W |
| **LED TECHNICS (LUMINAIRE)** | 288lm // 8,5W // 34lm/W |

**Requirements**

LED POWER SUPPLY 200 mA - DC

**Accessories**

COMPO S HONEYCOMB SINGLE USE B
COMPO S LINEAR SPREAD LENS
COMPO S SPREAD LENS
COMPO S SOFTENING LENS
COMPO S GLASS SBL

For detailed installation instructions, please consult the manual : **9_15721_XXX0_HAND.pdf**

DELTALIGHT

# COMPO S HP TW 96520

9 15721 9020 B

## CEILING COMPATIBILITY

| Ceiling Type | Mounting Kit | |
|---|---|---|
|  System ceiling | 15710 0010 - MOUNTING KIT COMPO S TRIM | Required |
| | 15710 0040 - MOUNTING KIT COMPO S TRIMLESS | Required |
|  Plasterboard | 15710 0010 - MOUNTING KIT COMPO S TRIM | Required |
| | 15710 0040 - MOUNTING KIT COMPO S TRIMLESS | Required |
|  Wood | 15710 0010 - MOUNTING KIT COMPO S TRIM | Required |
| | 15710 0040 - MOUNTING KIT COMPO S TRIMLESS | Required |

## FINISH YOUR SPECIFICATION

### LED Power supply

### # of Fixtures

**Min current | Max current**

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

**15710 5800** LED POWER SUPPLY MULTIPOWER 12W DALI DT8 200mA — 1 ☐

### Mounting kits




**15710 0010 B** MOUNTING KIT COMPO S TRIM B ☐

**Cutout dimension (mm): 55**

**15710 0010 W** MOUNTING KIT COMPO S TRIM W ☐




**15710 0040** MOUNTING KIT COMPO S TRIMLESS ☐

**Cutout dimension (mm): 55**

### Light altering devices

**15710 0100 B** COMPO S HONEYCOMB SINGLE USE B ☐

**15710 0110** COMPO S LINEAR SPREAD LENS ☐

DELTALIGHT

# COMPO S HP TW 96520

9 15721 9020 B

**Cutout dimension (mm): 26,5**

**15710 0120** COMPO S SPREAD LENS ☐

**Cutout dimension (mm): 26,5**

**15710 0130** COMPO S SOFTENING LENS ☐

**Cutout dimension (mm): 26,5**

**15710 0140** COMPO S GLASS SBL ☐

**Cutout dimension (mm): 26,5**

Notes: