



MULTINOVA 30 PIVOT 930



27928 9300 B

AVAILABLE IN

BLACK 27928 9300 B

GOLD COLOURED 27928 9300 GC

WHITE 27928 9300 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	2.1
ADJUSTABILITY	0° to 45° swiveling, 360° rotatable
INFORMATION	INCL.PC SBL INCL.LED POWER SUPPLY - 2 power settings

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	HO: LED cluster 14,9W / CRI>90 (R9: 68) / 3000K / 2174lm Or LED cluster 9,8W / CRI>90 (R9: 68) / 3000K / 1358lm
TM-30 VALUES	Rf: 89 / Rg: 97 rf: 89 / Rg: 97
SDCM	SDCM3
RISKGROUP	RG0
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	HO: 2174lm // 14,9W // 146lm/W Or 1358lm // 9,8W // 139lm/W
LED TECHNICS (LUMINAIRE)	HO: 1580lm // 17,1W // 92lm/W Or 987lm // 11,3W // 88lm/W

For detailed installation instructions, please consult the manual : [27928_XXX0_HAND.pdf](#)

DELTALIGHT

MULTINOVA 30 PIVOT 930

27928 9300 B

Notes: