
DELTALIGHT




SOLI - 52 92720 Q-DIM

REFERENCE 27118 922Q B

AVAILABLE IN
BLACK 27118 922Q B
GOLD COLOURED 27118 922Q GC
WHITE 27118 922Q W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 90° swiveling, 360° rotatable
INFORMATION	REFLECTOR FL-20° EXCL.LED POWER SUPPLY 48V-DC Optional REFLECTORS 30° & 45° available

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	Qbus dim
ENERGY CLASS	E
CERTIFICATES	CB, ENEC, LCA

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 10,3W / CRI>90 (R9: 60) / 2700K / 1224lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	20°
LED TECHNICS (LIGHT SOURCE)	1224lm // 10,3W // 119lm/W
LED TECHNICS (LUMINAIRE)	767lm // 11,8W // 65lm/W

Requirements

SPY 52 TUBE
LED POWER SUPPLY 48V-DC

Accessories

HONEYCOMB 42
SPREAD LENS 42
LINEAR SPREAD LENS 42
SOFTENING LENS 42
GLASS SBL 42

DELTALIGHT

SOLI - 52 92720 Q-DIM

27118 922Q B

For detailed installation instructions, please consult the manual : **27118_XXXQ_HAND.pdf**


FINISH YOUR SPECIFICATION

LED power supplies

of Fixtures


ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 9

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 23


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 9

Dimtype: non-dimmable

Cutout dimension (mm): 40




21012 0240 LED POWER SUPPLY 48V-DC / 200W — 19


Dimtype: non-dimmable

Cutout dimension (mm): 40

Light altering devices



19810 0010 B HONEYCOMB 42 SINGLE USE B




19810 0020 LINEAR SPREAD LENS 42

DELTALIGHT

SOLI - 52 92720 Q-DIM


27118 922Q B




19810 0030 SPREAD LENS 42



19810 0040 SOFTENING LENS 42



19810 0050 GLASS SBL 42



19810 0060 B HONEYCOMB 42 DOUBLE USE B

Finish your product



19810 0100 B SPY 52 TUBE B

19810 0100 FBR SPY 52 TUBE FBR

19810 0100 FG SPY 52 TUBE FG

19810 0100 GC SPY 52 TUBE GC

19810 0100 W SPY 52 TUBE W

Replaceable reflector / lens



19810 0180 SPY 52 REFLECTOR 20°


DELTALIGHT

SOLI - 52 92720 Q-DIM

27118 922Q B





19810 0190 SPY 52 REFLECTOR 45°



19810 0240 SPY 52 REFLECTOR 30°

COMPATIBLE COMPOSABLES

SOLISCAPE profile	Available Colours
 **27111 0020** SOLI - PROFILE 2m	
 **27111 0030** SOLI - PROFILE 3m	

Notes: