

DEEP RINGO DYNAMIC FOCUS TRIMLESS 927

32112 9200 BRCU

BESCHIKBAAR IN

ZWART 32112 9200 B

ALU GEBORSTELD 32112 9200 BRA

GEBORSTELD ANTRACIET 32112 9200 BRAT

GEBORSTELD BRUIN BRONS 32112 9200 BRBB

GEBORSTELD KOPER 32112 9200 BRCU


GEBORSTELD GOUD 32112 9200 BRG

GEBORSTELD OUD BRONS 32112 9200 BROB

CRÈME 32112 9200 CR

PIANO ZWART 32112 9200 PB

WIT 32112 9200 W



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
INSTALLATIE	Plafond Inbouw
ZAAGMAAT/OPENING (MM)	rond - Ø KIT
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0.3
RICHTBAARHEID	niet richtbaar

Elektrische info

KLASSE	III
DIM TYPE	afhankelijk van de te kiezen externe voeding
ENERGIE KLASSE	G

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	13° (central part only): LED array 5,8W / CRI>90 (R9: 56) / 2700K / 528lm Or 24° central part: LED array 1W / CRI>90 (R9: 56) / 2700K / 63lm 24° ring part: LED cluster 5,5W / CRI>90 (R9: 50) / 2700K / 868lm
TM-30 WAARDEN	13° (central part only): rf: 91 / Rg: 99 24° central part: rf: 91 / Rg: 99 24° ring part: rf: 93 / Rg: 100
SMDC	SDCM2 SDCM3
RISK-GROEP	RG2 (threshold 0,6m) RG1
LM80	L90B10 > 41000 L80 > 60000
BEAMANGLE	13°-24°
LED TECHNIEK (LICHTBRON)	13° (central part only): 528lm // 5,8W // 94lm/W Or 24° central part: 63lm // 1W // 100lm/W 24° ring part: 868lm // 5,5W // 158lm/W
LED TECHNIEK (TOESTEL)	13° (central part only): 475lm // 6,7W // 71lm/W Or 24° ring part: 347lm // 6,3W // 55lm/W

DEEP RINGO DYNAMIC FOCUS TRIMLESS 927

32112 9200 BRCU

Benodigdheden

MOUNTING KIT R82 TRIMLESS O.F.A.
LED POWER SUPPLY DYNAMIC FOCUS

Voor gedetailleerde montage gegevens, consulteer de handleiding : [32112_XXX0_HAND.pdf](#)

PLAFOND COMPATIBILITEIT

Ceiling Type	Mounting Kit	
 System ceiling	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Plasterboard	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Stucanet	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Concrete + plaster	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Lintel + plaster	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Hollow-core slab + plaster	 15212 2000 - MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Ventilation in plasterboard	 29810 0100 - MOUNTING KIT SIDE AIR ONLY 1	Required
	 29810 0050 - MOUNTING KIT NO AIR 101	Required
	 29810 0010 - MOUNTING KIT SIDE AIR 101	Required
 Ventilation in concrete + plaster	 29810 0210 - MOUNTING KIT TOP AIR 101	Required
	 29810 0050 - MOUNTING KIT NO AIR 101	Required
	 29810 0200 - MOUNTING KIT TOP AIR ONLY 1	Required
 Cold stretched ceiling	 15212 0070 - MOUNTING KIT R82 TRIMLESS CSC	Required
 Warm stretched ceiling	 15212 0150 - MOUNTING KIT R82 TRIMLESS WSC	Required


DEEP RINGO DYNAMIC FOCUS TRIMLESS 927


32112 9200 BRCU

VERVOLLEDIG UW SPECIFICATIE

LED voedingen	# armaturen
 # armaturen geeft aan hoeveel toestellen op de voeding kunnen worden aangesloten (min -> max). De waarden vóór en na de 'l' komen respectievelijk overeen met de minimale en maximale aanstroom. Waarden tussen haakjes zijn van toepassing op 110V.	Min. stroom Max. stroom

 32110 0015 LED POWER SUPPLY DYNAMIC FOCUS DIM5	3
 32110 0020 LED POWER SUPPLY DYNAMIC FOCUS + WIRELESS CONTROL DIM5	3
Dimtype: DALI Uitsparingsmaat (mm): 75	

 15212 2000 MOUNTING KIT R82 TRIMLESS O.F.A.	
Uitsparingsmaat (mm): 105	

 15212 0070 MOUNTING KIT R82 TRIMLESS CSC	
 15212 0150 MOUNTING KIT R82 TRIMLESS WSC	

Notes: