



OML50 - INFORM DU TW 1312mm 8+8LED 95063 DIM5

31448 9035 B

BESCHIKBAAR IN
ZWART 31448 9035 B



[Bekijk op website](#)



Algemene info

| | |
|-------------------------------|---|
| LOCATIE | binnen |
| STOF EN WATERDICHTHEID | IP20 |
| GEWICHT (KG) | 1.9 |
| INFO | INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT |

Elektrische info

| | |
|------------------------|----------------------|
| INGANGSSPANNING | 220-240V / 0 50-60Hz |
| KLASSE | I |
| VOEDING | YES |
| DIM TYPE | DALI |
| ENERGIE KLASSE | E |
| CERTIFICATEN | EPD, RCM |

Info lichtbron

| | |
|---------------------------------|--|
| LIGHTSOURCE NAME | LED |
| LICHTBRON | DOWN @ 2700K: LED cluster 14,9W / CRI>90 (R9: 50) / 2700K-5000K / 1952lm UP @ 2700K: LED cluster 14,9W / CRI>90 (R9: 50) / 2700K-5000K / 1952lm Or DOWN @ 5000K: LED cluster 13,5W / CRI>90 (R9: 50) / 2700K-5000K / 2336lm UP @ 5000K: LED cluster 13,5W / CRI>90 (R9: 50) / 2700K-5000K / 2336lm |
| SDCM | SDCM3 |
| RISK-GROEP | RG1 |
| LM80 | L80 > 60000 |
| BEAMANGLE | 63° |
| LED TECHNIEK (LICHTBRON) | DOWN @ 2700K: 1952lm // 14,9W // 131lm/W UP @ 2700K: 1952lm // 14,9W // 131lm/W Or DOWN @ 5000K: 2336lm // 13,5W // 173lm/W UP @ 5000K: 2336lm // 13,5W // 173lm/W |

Opties

WIRELESS CONTROL DIM5

DELTALIGHT

OML50 - INFORM DU TW 1312mm 8+8LED 95063 DIM5

31448 9035 B

Notes: