



OML50 - INFORM DU TW 1312mm 8+8LED 95063 DIM5

31448 9035 B

AVAILABLE IN
BLACK 31448 9035 B



[View on website](#)



General info

LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.9
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 2700K: LED cluster 14,9W / CRI>90 (R9: 50) / 2700K-5000K / 1952lm UP @ 2700K: LED cluster 14,9W / CRI>90 (R9: 50) / 2700K-5000K / 1952lm Or DOWN @ 5000K: LED cluster 13,5W / CRI>90 (R9: 50) / 2700K-5000K / 2336lm UP @ 5000K: LED cluster 13,5W / CRI>90 (R9: 50) / 2700K-5000K / 2336lm
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNICS (LIGHT SOURCE)	DOWN @ 2700K: 1952lm // 14,9W // 131lm/W UP @ 2700K: 1952lm // 14,9W // 131lm/W Or DOWN @ 5000K: 2336lm // 13,5W // 173lm/W UP @ 5000K: 2336lm // 13,5W // 173lm/W

Options

WIRELESS CONTROL DIM5

DELTALIGHT

OML50 - INFORM DU TW 1312mm 8+8LED 95063 DIM5

31448 9035 B

Notes: