




COMPO S HP 93010

9 15719 9310 B

AVAILABLE IN
NEGRO 9 15719 9310 B
CHROMO 9 15719 9310 C
CHROMO OSCURO 9 15719 9310 DC
BLANCO 9 15719 9310 W



[View on website](#)



EXCLUSIVELY AVAILABLE IN INDIA

General info	
LOCATION	interior
INSTALLATION	Techo Empotrado
CUTOUT SHAPE/SIZE (MM)	redondo - 120
RECESSED DEPTH (MM)	114
THICKNESS OF MOUNTING SURFACE (MM)	max.25
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.166
ADJUSTABILITY	0° to 30° giratorio, 355° orientable
INFORMATION	Accessories are not applicable with Super Spot except Honeycomb Single use B

Electrical info	
CLASS	III
DIM TYPE	dependiendo del tipo de fuente de alimentación externa
ENERGY CLASS	G

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 4,7W / CRI>90 / 3000K / 371lm
BEAMANGLE	10°
LED TECHNICS (LIGHT SOURCE)	371lm // 4,7W // 80lm/W
LED TECHNICS (LUMINAIRE)	239lm // 5,4W // 44lm/W

Requirements	
LED POWER SUPPLY 500 mA - DC	

Accessories	
COMPO S HONEYCOMB SINGLE USE B	
COMPO S LINEAR SPREAD LENS	
COMPO S SPREAD LENS	
COMPO S SOFTENING LENS	
COMPO S GLASS SBL	

For detailed installation instructions, please consult the manual : [9_15719_XXX0_HAND.pdf](#)

DELTALIGHT

COMPO S HP 93010

9 15719 9310 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required
	 15710 0010 - MOUNTING KIT COMPO S TRIM	Required
	 15710 0040 - MOUNTING KIT COMPO S TRIMLESS	Required

FINISH YOUR SPECIFICATION

Fuente de alimentación LED

of Fixtures



of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current

15710 3100	LED POWER SUPPLY 18W NO DIM 1400mA	1->4	☐
15710 3400	LED POWER SUPPLY MULTIPOWER 25W NO DIM 500mA	1->2	☐
15710 3900	LED POWER SUPPLY MULTIPOWER 10W DIM8 500mA	1	☐
15710 4600	LED POWER SUPPLY MULTIPOWER 12W DIM1 500mA	1	☐
15710 5000	LED POWER SUPPLY MULTIPOWER 55W DALI DT6 1400mA	1->13	☐
Dimtype: con DALI			
15710 5400	LED POWER SUPPLY MULTIPOWER 20W DALI DT6 500mA	1->2	☐
Dimtype: con DALI			

Mounting Kit



15710 0010 B MOUNTING KIT COMPO S TRIM B

☐

Cutout dimension (mm): 55

15710 0010 W MOUNTING KIT COMPO S TRIM W

☐

COMPO S HP 93010

9 15719 9310 B



15710 0040 MOUNTING KIT COMPO S TRIMLESS

☐

Cutout dimension (mm): 55

Dispositivos de modificación de Luz

15710 0100 B COMPO S HONEYCOMB SINGLE USE B

☐

15710 0110 COMPO S LINEAR SPREAD LENS

☐

Cutout dimension (mm): 26,5

15710 0120 COMPO S SPREAD LENS

☐

Cutout dimension (mm): 26,5

15710 0130 COMPO S SOFTENING LENS

☐

Cutout dimension (mm): 26,5

15710 0140 COMPO S GLASS SBL

☐

Cutout dimension (mm): 26,5

Notes: