



## NOCTA SQ155 2VWFL 930

30124 9300 N

AVAILABLE IN



**ALU GREY** 30124 9300 A

**BLACK** 30124 9300 B

**FLEMISH BRONZE OUTDOOR** 30124 9300 FBRX

**ANTHRACITE** 30124 9300 N

**WHITE** 30124 9300 W



[View on website](#)



### General info

|                                             |                                                  |
|---------------------------------------------|--------------------------------------------------|
| <b>LOCATION</b>                             | outdoor                                          |
| <b>INSTALLATION</b>                         | Wall Surface mounted                             |
| <b>INGRESS PROTECTION</b>                   | IP65                                             |
| <b>PROTECTION AGAINST MECHANICAL IMPACT</b> | IK06                                             |
| <b>WEIGHT (KG)</b>                          | 1.8                                              |
| <b>ADJUSTABILITY</b>                        | non adjustable                                   |
| <b>INFORMATION</b>                          | INCL.2 x TUBE<br>INCL.LED POWER SUPPLY 700 mA-DC |

### Electrical info

|                     |                    |
|---------------------|--------------------|
| <b>ELECTRICAL</b>   | 100-240V / 50-60Hz |
| <b>CLASS</b>        | I                  |
| <b>POWER SUPPLY</b> | YES                |
| <b>DIM TYPE</b>     | non-dimmable       |
| <b>ENERGY CLASS</b> | F                  |
| <b>CERTIFICATES</b> | CB, ENEC, EPD, RCM |

### Lightsource info

|                                    |                                                      |
|------------------------------------|------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                  |
| <b>LIGHTSOURCE</b>                 | 2 x (LED array 2W / CRI>90 (R9: 60) / 3000K / 240lm) |
| <b>TM-30 VALUES</b>                | rf: 92 / Rg: 99                                      |
| <b>SDCM</b>                        | SDCM3                                                |
| <b>RISKGROUP</b>                   | RG2                                                  |
| <b>LM80</b>                        | L90B10 > 150000                                      |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 480lm // 4W // 120lm/W                               |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 142lm // 4,6W // 31lm/W                              |

For detailed installation instructions, please consult the manual : [30124\\_XXX0\\_HAND.pdf](#)

# DELTALIGHT

## NOCTA SQ155 2VWFL 930

30124 9300 N

Notes: