

# M-INFORM



Pure minimalism Inform breaths refinement in all its aspects. A high performer, despite its minimalistic design, Inform does not compromise on performance.

Specification	
LED Aperture	$\frac{5}{8}$ "
Adjustability:	Fixed
Rating:	IP20

Performance	
LED Maintenance:	L80>60,000h
McAdam Step:	3
CRI:	90
*Inform L08 SP:	13W
*Inform L11 SP:	19W

Delivered Lumens	2700K	3000K	3500K
M-Inform L08:	1553Lm	1577Lm	1613Lm
M-Inform L11:	2203Lm	2235Lm	2287Lm

#### Listing

ETL certified to US and Canadian safety standards.

#### Warranty

5-year limited warranty.

## Ordering

ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: INFL11-SPFL35F-B-M-MDL

Luminaire	Shape	Length	Power*	Optic	CCT	Function	Finish	Application <sup>(1)</sup>	Controls
INF INFORM	L Linear	08 Linear 838mm / 33"  11 Linear 1114mm / 43 $\frac{7}{8}$ "	SP Standard Power	FL Flood 67°	27 2700K  30 3000K  35 3500K	F Fixed	B Black	M <sup>(2)</sup> Shiftline M26H / Shiftline M26H + SBL <sup>(3)</sup> / Shiftline M26L / Splitline M20 / Splitline M20 ST Profile	MDL <sup>(3)</sup> 0-10V dim via Modulator  D5 Dali dim  WD <sup>(3)</sup> Wireless dim

<sup>1</sup> Profile system hardware specified separately.

<sup>2</sup> Not compatible with Splitline M52; compatible with all other Shiftline & Splitline Magnetic Profiles.

<sup>3</sup> Shiftline M26H + SBL only available with Controls D5.


## Related Products

M-LED Line, M-LED Line Up, M-Dot.Com Wallwash, M-Dot.Com M4, Inform SQ, Inform R, Conform

Finish Options

M-INFORM L08

M-INFORM L11




20mm  
25/32"

27mm  
1"-1/16

838mm  
33"

For Application M  
(not compatible with Splitline M52 Profile)



20mm  
25/32"

27mm  
1"-1/16

1114  
43"-7/8



For Application M  
(not compatible with Splitline M52 Profile)



Photometric Data

INFORM L08

INFORM L11



Installation Options

Delta Light's Magnetic Systems all utilize 48V remote power supplies. With a maximum of 96W per power supply, the below details maximum magnetic modules per power feed.

Maximum Capacity per Remote Power Supply	L08	L11
*SP:	6	4

FOR SYSTEM HARDWARE, REFER TO THE FOLLOWING PROFILE SYSTEMS:  
Shiftline M26H (surface/suspended, high-height, optional curved corner connectors)  
Shiftline M26H + SBL (surface/suspended, high-height, integral continuous light line)  
Shiftline M26L (surface/suspended, low-height, stacking possible)  
Splitline M20 (recessed, knife-edge, optional curved corner connectors)  
Splitline M20 ST (recessed, small trim)

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.