M-INFORM



Pure minimalism Inform breaths refinement in all its aspects. A high performer, despite its minimalistic design, Inform does not compromise on performance.

Specification	
LED Aperture:	5/8"
Adjustability:	Fixed
Rating:	Damp

Performance	
CRI:	90
SDCM:	3
LED Maintenance:	L80>60,000h
*Standard Power Length 08:	13.3W
*Standard Power Length 11:	19.1W

Delivered Lumens	2700K	3000K	3500K
M-Inform L08:	1553	1577	1613
M-Inform L11:	2203	2235	2287

Listing
ETL certified to US and Canadian safety standards.

Warranty
5-year limited warranty.

Ordering
ALL BOXES MUST BE FILLED IN TO CORRECTLY ORDER

Example: INFL11-SPFL35F-B-M-MDL

Luminaire	Shape	Length	Power*	Optic	CCT	Function	Finish	Application[1]	Controls
INF INFORM	**L** Linear	**08** Linear 838mm / 33" **11** Linear 1114mm / 43 7/8"	**SP** Standard Power	**FL** Flood 67°	**27** 2700K **30** 3000K **35** 3500K	**F** Fixed	**B** Black	**M**[2] Shiftline M26H / Shiftline M26H + SBL[3]/ Shiftline M26L / Splitline M20 / Splitline M20 ST Profile	**MDL**[3] 0-10V dim via Modulator **D5** Dali dim **WD**[3] Wireless dim


1 Low voltage system hardware specified separately.
2 Not compatible with Splitline M52; compatible with all other Shiftline & Splitline low voltage systems.
3 Shiftline M26H + SBL only available with Controls D5.

Related Products

M-LED Line, M-LED Line Up, M-Dot.Com Wallwash, M-Dot.Com M4, Inform SQ, Inform R, Conform


Finish Options

M-INFORM L08



For Application M
(not compatible with Splitline M52 Profile)

M-INFORM L11




For Application M
(not compatible with Splitline M52 Profile)



(Shown in Shiftline M26H)


Photometric Data

INFORM L08



FL 67°

INFORM L11



FL 67°

Installation Options

Delta Light's Magnetic Systems all utilize 48V remote power supplies. With a maximum of 96W per power supply, the below details maximum magnetic modules per power feed.

Maximum Capacity per Remote Power Supply	Length 08	Length 11
*Standard Power:	6	4

FOR SYSTEM HARDWARE, REFER TO THE FOLLOWING PROFILE SYSTEMS:
Shiftline M26H (surface/suspended, high-height, optional curved corner connectors)
Shiftline M26H + SBL (surface/suspended, high-height, integral continuous light line)
Shiftline M26L (surface/suspended, low-height, stacking possible)
Splitline M20 (recessed, knife-edge, optional curved corner connectors)
Splitline M20 ST (recessed, small trim)

As technology changes, please use information above as guidance. For most recent updated information please contact factory. Specifications subject to change without notice.