



OML50 - PRISMATIC LENS DU HO  
656mm 940 DIM5

31632 9405 B

AVAILABLE IN  
BLACK 31632 9405 B

 [View on website](#)



|                             |                                                                                                                        |
|-----------------------------|------------------------------------------------------------------------------------------------------------------------|
| General info                |                                                                                                                        |
| LOCATION                    | indoor                                                                                                                 |
| INGRESS PROTECTION          | IP20                                                                                                                   |
| WEIGHT (KG)                 | 1                                                                                                                      |
| INFORMATION                 | INCL.DIMMABLE LED POWER SUPPLY<br>(DALI-2 standard)<br>CABLING 1 CIRCUIT                                               |
| Electrical info             |                                                                                                                        |
| ELECTRICAL                  | 220-240V / 0 50-60Hz                                                                                                   |
| CLASS                       | I                                                                                                                      |
| POWER SUPPLY                | YES                                                                                                                    |
| DIM TYPE                    | DALI                                                                                                                   |
| ENERGY CLASS                | D                                                                                                                      |
| CERTIFICATES                | EPD, RCM                                                                                                               |
| Lightsource info            |                                                                                                                        |
| LIGHTSOURCE NAME            | LED                                                                                                                    |
| LIGHTSOURCE                 | DOWN: LED cluster 15,5W / CRI>90 (R9: 50) / 4000K / 2425lm<br>UP: LED cluster 12,1W / CRI>90 (R9: 50) / 4000K / 1821lm |
| TM-30 VALUES                | Rf: 90 / Rg: 101                                                                                                       |
| SDCM                        | SDCM3                                                                                                                  |
| RISKGROUP                   | RG1                                                                                                                    |
| LM80                        | L80 > 60000                                                                                                            |
| LED TECHNICS (LIGHT SOURCE) | DOWN: 2425lm // 15,5W // 160lm/W<br>UP: 1821lm // 12,1W // 151lm/W                                                     |
| Options                     |                                                                                                                        |
| WIRELESS CONTROL DIM5       |                                                                                                                        |

Notes: