
DELTALIGHT




SPL14 - SPY 20 92730 MDL

REFERENCE 27311 9220 W

AVAILABLE IN
BLACK 27311 9220 B
FLEMISH BRONZE 27311 9220 FBR
FLEMISH GOLD 27311 9220 FG
GOLD COLOURED 27311 9220 GC
WHITE 27311 9220 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.1
ADJUSTABILITY	0° to 90° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-30° EXCL.LED POWER SUPPLY 48V-DC SPY 20 TUBE B included

Electrical info	
ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 2W / CRI>90 (R9: 55) / 2700K / 220lm
TM-30 VALUES	Rf: 91 / Rg: 99
SDCM	SDCM3
RISKGROUP	RG2
LM80	L90B10 > 150000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	220lm // 2W // 110lm/W
LED TECHNICS (LUMINAIRE)	166lm // 2,3W // 72lm/W

Requirements

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

For detailed installation instructions, please consult the manual : **27311_XXX0_HAND.pdf**

DELTALIGHT

SPL14 - SPY 20 92730 MDL

27311 9220 W


FINISH YOUR SPECIFICATION

SMART 48

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.



300 90 011 SMART 48 MODULATOR DIM9 — 72

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD — 72


Dimtype: WDL = wireless dimmable

LED power supplies

# of Fixtures


Min current | Max current

ⓘ # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.




300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN — 37

Dimtype: non-dimmable



300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN — 90


Dimtype: non-dimmable



21012 0230 LED POWER SUPPLY 48V-DC / 100W — 37

Dimtype: non-dimmable

Cutout dimension (mm): 40



21012 0240 LED POWER SUPPLY 48V-DC / 200W — 75

Dimtype: non-dimmable


Cutout dimension (mm): 40



DELTALIGHT

SPL14 - SPY 20 92730 MDL

27311 9220 W

COMPATIBLE COMPOSABLES

D-LINER SHIFTLINE 19	Available Colours
 **29110 0010** D-LINER 19 SL PROFILE SET SAPP 2m	
 **29110 0030** D-LINER 19 SL PROFILE SET 30BD 2m	

SPLITLINE 14 profile	Available Colours
 **27300 0020** SPL14 - PROFILE 2m	
 **27300 0030** SPL14 - PROFILE 3m	

Notes: