




OML50 - INFORM DU TW 1640mm 8+8LED 95063 DIM5

31449 9035 B

BESCHIKBAAR IN
ZWART 31449 9035 B



[Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	2.1
INFO	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

Elektrische info

ELEKTRISCH	220-240V / 0 50-60Hz
KLASSE	I
VOEDING INBEGREPEN	YES
DIM TYPE	DALI
ENERGIE KLASSE	E
CERTIFICATES	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN @ 2700K: LED cluster 14,9W / CRI>90 (R9: 50) / 2700K-5000K / 1952lm UP @ 2700K: LED cluster 18,6W / CRI>90 (R9: 50) / 2700K-5000K / 2440lm Or DOWN @ 5000K: LED cluster 13,5W / CRI>90 (R9: 50) / 2700K-5000K / 2336lm UP @ 5000K: LED cluster 16,9W / CRI>90 (R9: 50) / 2700K-5000K / 2920lm
SMDC	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNIEK (LICHTBRON)	DOWN @ 2700K: 1952lm // 14,9W // 131lm/W UP @ 2700K: 2440lm // 18,6W // 131lm/W Or DOWN @ 5000K: 2336lm // 13,5W // 173lm/W UP @ 5000K: 2920lm // 16,9W // 173lm/W

Opties

WIRELESS CONTROL DIM5

DELTALIGHT

OML50 - INFORM DU TW 1640mm 8+8LED 95063 DIM5

31449 9035 B

Notes: