



OML50 - PRISMATIC LENS DU HO 984mm 930 DIM5

31633 9305 B

BESCHIKBAAR IN
ZWART 31633 9305 B

 [Bekijk op website](#)



Algemene info

LOCATIE	binnen
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	1.5
INFO	INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Elektrische info

INGANGSSPANNING	220-240V / 0 50-60Hz
KLASSE	I
VOEDING	YES
DIM TYPE	DALI
ENERGIE KLASSE	D
CERTIFICATEN	EPD, RCM

Info lichtbron

LIGHTSOURCE NAME	LED
LICHTBRON	DOWN: LED cluster 23,3W / CRI>90 (R9: 50) / 3000K / 3570lm UP: LED cluster 18,1W / CRI>90 (R9: 50) / 3000K / 2621lm
TM-30-15 WAARDEN	Rf: 92 / Rg: 100
SDCM	SDCM3
RISK-GROEP	RG1
LM80	L80 > 60000
LED TECHNIEK (LICHTBRON)	DOWN: 3570lm // 23,3W // 153lm/W UP: 2621lm // 18,1W // 145lm/W

Opties

WIRELESS CONTROL DIM5

Notes: