DELTALIGHT



OML50 - PRISMATIC LENS DU HO 984mm 930 DIM5

REFERENCE 31633 9305 B

AVAILABLE IN
BLACK 31633 9305 B

View on website

General info	
LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.5
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI-2 standard) CABLING 1 CIRCUIT

Electrical info	
ELECTRICAL	220-240V / 0|50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 23,3W / CRI>90 (R9: 50) / 3000K / 3570lm UP: LED cluster 18,1W / CRI>90 (R9: 50) / 3000K / 2621lm
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 3570lm // 23,3W // 153lm/W UP: 2621lm // 18,1W // 145lm/W

Options

WIRELESS CONTROL DIM5

Notes: