



M26L - SPY 52 92730 MDL

23274 9240 W

AVAILABLE IN


BLACK 23274 9240 B

FLEMISH BRONZE 23274 9240 FBR

FLEMISH GOLD 23274 9240 FG

GOLD COLOURED 23274 9240 GC

WHITE 23274 9240 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Low voltage systems Low voltage system mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.4
ADJUSTABILITY	0° to 90° swiveling, 360° rotatable
INFORMATION	REFLECTOR FL-30° EXCLLED POWER SUPPLY 48V-DC Optional REFLECTORS 20° & 45° available

Electrical info

ELECTRICAL	48V-DC
CLASS	III
DIM TYPE	MDL = 1-10V or DALI or push button
ENERGY CLASS	F
CERTIFICATES	CB, ENEC, EPD

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 12,4W / CRI>90 (R9: 60) / 2700K / 1403lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
BEAMANGLE	30°
LED TECHNICS (LIGHT SOURCE)	1403lm // 12,4W // 113lm/W
LED TECHNICS (LUMINAIRE)	895lm // 14,3W // 63lm/W

Remarks

Take a look at our MAGNETIC PROFILES movie

Requirements

SPY 52 TUBE

LED POWER SUPPLY 48V-DC

Options

DIMMABLE MODULATOR

Accessories

HONEYCOMB 42

SPREAD LENS 42

Delta Light NV may revise the information and technical data at any time without notice. Version: 29/04/2026

M26L - SPY 52 92730 MDL

23274 9240 W

LINEAR SPREAD LENS 42
SOFTENING LENS 42
GLASS SBL 42

For detailed installation instructions, please consult the manual : [23274_XXX0_HAND.pdf](#)


FINISH YOUR SPECIFICATION

Current supply

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



21032 0030 SMART 48 MODULATOR PLUG-IN WD

13


Dimtype: WDL = wireless dimmable

SMART 48

of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



300 90 011 SMART 48 MODULATOR DIM9

13

Dimtype: 1-10V or DALI or push button



300 90 012 SMART 48 MODULATOR WD

13

Dimtype: WDL = wireless dimmable

LED power supplies

of Fixtures





 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current





DELTALIGHT

M26L - SPY 52 92730 MDL

23274 9240 W

	300 89 48 100 LED POWER SUPPLY 48V-DC / 100W DIN	7	☐
Dimtype: non-dimmable			
	300 89 48 240 LED POWER SUPPLY 48V-DC / 240W DIN	16	☐
Dimtype: non-dimmable			
	21012 0230 LED POWER SUPPLY 48V-DC / 100W	7	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 40			
	21012 0240 LED POWER SUPPLY 48V-DC / 200W	14	☐
Dimtype: non-dimmable			
Cutout dimension (mm): 40			

Light altering devices

	19810 0010 B HONEYCOMB 42 SINGLE USE B		☐
	19810 0020 LINEAR SPREAD LENS 42		☐
	19810 0030 SPREAD LENS 42		☐
	19810 0040 SOFTENING LENS 42		☐
	19810 0050 GLASS SBL 42		☐


DELTALIGHT

M26L - SPY 52 92730 MDL

23274 9240 W

 14 Ø42	19810 0060 B HONEYCOMB 42 DOUBLE USE B	☐
---	--	--------------------------

Finish your product

 40 Ø49	19810 0100 B SPY 52 TUBE B	☐
	19810 0100 FBR SPY 52 TUBE FBR	☐
	19810 0100 FG SPY 52 TUBE FG	☐
	19810 0100 GC SPY 52 TUBE GC	☐
	19810 0100 W SPY 52 TUBE W	☐

Replaceable reflector / lens









 18 Ø45	19810 0180 SPY 52 REFLECTOR 20°	☐
 18 Ø45	19810 0190 SPY 52 REFLECTOR 45°	☐
 18 Ø45	19810 0240 SPY 52 REFLECTOR 30°	☐

DELTALIGHT

M26L - SPY 52 92730 MDL

23274 9240 W

COMPATIBLE COMPOSABLES

SHIFTLINE M26L profile (+ SHIFTLINE M26L MATRIX)		Available Colours
	23358 0000 SLM26L - PROFILE	 
	23358 0010 SLM26L - PROFILE 1m	 
	23358 0020 SLM26L - PROFILE 2m	         
	23358 0030 SLM26L - PROFILE 3m	         
SHIFTLINE M35R profile		Available Colours
	23375 0000 SLM35R - PROFILE	
	23375 0010 SLM35R - PROFILE 1m	
	23375 0020 SLM35R - PROFILE 2m	
	23375 0030 SLM35R - PROFILE 3m	

Notes:

DELTALIGHT

M26L - SPY 52 92730 MDL

23274 9240 W