
DELTALIGHT




MULTINOVA 30 SOFT 930 DIM5

REFERENCE 27916 9005 GC

AVAILABLE IN
BLACK 27916 9005 B
GOLD COLOURED 27916 9005 GC
WHITE 27916 9005 W





View on website

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed,Ceiling Surface mounted,Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.8
ADJUSTABILITY	non adjustable
INFORMATION	INCL.PC SBL INCL.DIMMABLE LED POWER SUPPLY

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, EPD, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 14,5W / CRI>90 (R9: 50) / 3000K-1800K / 2188lm
TM-30 VALUES	Rf: 89,4 / Rg: 98,6
SDCM	SDCM3
RISKGROUP	RG1
LM80	L70 > 60000
LED TECHNICS (LIGHT SOURCE)	2188lm // 14,5W // 151lm/W
LED TECHNICS (LUMINAIRE)	1590lm // 16,7W // 95lm/W

Options

MULTINOVA 30 SUSPENSION SET
MULTINOVA 30 RECESSED KIT

For detailed installation instructions, please consult the manual : **27916_XXX5_HAND.pdf**

DELTALIGHT

MULTINOVA 30 SOFT 930 DIM5


27916 9005 GC

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 **System ceiling**	27910 0050 - MULTINOVA 30 RECESSED KIT	Required
 **Plasterboard**	27910 0050 - MULTINOVA 30 RECESSED KIT	Required
 **Stucanet**	27910 0050 - MULTINOVA 30 RECESSED KIT	Required
 **Concrete + plaster**	27910 0050 - MULTINOVA 30 RECESSED KIT	Required
 **Lintel + plaster**	27910 0050 - MULTINOVA 30 RECESSED KIT	Required
 **Hollow-core slab + plaster**	27910 0050 - MULTINOVA 30 RECESSED KIT	Required

FINISH YOUR SPECIFICATION

Recessed kits



27910 0050 MULTINOVA 30 RECESSED KIT ☐



Cutout dimension (mm): 341

Suspension parts



27910 0020 B MULTINOVA 30 SUSPENSION SET 5x0,75 3m B ☐

27910 0020 W MULTINOVA 30 SUSPENSION SET 5x0,75 3m W ☐

Notes:

MULTINOVA 30 SOFT 930 DIM5

27916 9005 GC