



OML50 - INFORM DU TW 2624mm 8+16+8LED 95063 DIM5

31451 9035 B

AVAILABLE IN
BLACK 31451 9035 B

 [View on website](#)



General info

LOCATION	indoor
INGRESS PROTECTION	IP20
WEIGHT (KG)	3.4
INFORMATION	INCL.DIMMABLE LED POWER SUPPLY (DALI DT8) CABLING 1 CIRCUIT

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E
CERTIFICATES	EPD, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 2700K: LED cluster 29,8W / CRI>90 (R9: 50) / 2700K-5000K / 3904lm UP @ 2700K: LED cluster 29,8W / CRI>90 (R9: 50) / 2700K-5000K / 3904lm Or DOWN @ 5000K: LED cluster 27W / CRI>90 (R9: 50) / 2700K-5000K / 4672lm UP @ 5000K: LED cluster 27W / CRI>90 (R9: 50) / 2700K-5000K / 4672lm
SDCM	SDCM3
RISKGROUP	RG1
BEAMANGLE	63°
LED TECHNICS (LIGHT SOURCE)	DOWN @ 2700K: 3904lm // 29,8W // 131lm/W UP @ 2700K: 3904lm // 29,8W // 131lm/W Or DOWN @ 5000K: 4672lm // 27W // 173lm/W UP @ 5000K: 4672lm // 27W // 173lm/W

Options

WIRELESS CONTROL DIM5

Notes:

DELTALIGHT

OML50 - INFORM DU TW 2624mm 8+16+8LED 95063 DIM5

31451 9035 B