



LOGIC LINEAR 440 92740 DIM5

30811 9235 N

AVAILABLE IN  
ANTHRACITE 30811 9235 N



[View on website](#)



|                                      |                                                                                                                                                     |
|--------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| General info                         |                                                                                                                                                     |
| LOCATION                             | outdoor                                                                                                                                             |
| INSTALLATION                         | Floor Recessed                                                                                                                                      |
| CUTOUT SHAPE/SIZE (MM)               | rectangle - BOX                                                                                                                                     |
| RECESSED DEPTH (MM)                  | 140                                                                                                                                                 |
| INGRESS PROTECTION                   | IP67                                                                                                                                                |
| PROTECTION AGAINST MECHANICAL IMPACT | IK09                                                                                                                                                |
| WEIGHT (KG)                          | 2                                                                                                                                                   |
| ADJUSTABILITY                        | non adjustable                                                                                                                                      |
| INFORMATION                          | 8 x LENS WFL-40°<br>INCL.DIMMABLE LED POWER SUPPLY 650mA-DC<br>INCL.1 x CABLE H07 RN-F 5 x 1mm² 0,5m<br>INCL.IP68 CONNECTOR 5P<br>ESG 8mm max.500kg |
| Electrical info                      |                                                                                                                                                     |
| ELECTRICAL                           | 220-240V / 0 50-60Hz                                                                                                                                |
| CLASS                                | I                                                                                                                                                   |
| POWER SUPPLY                         | YES                                                                                                                                                 |
| DIM TYPE                             | DALI                                                                                                                                                |
| ENERGY CLASS                         | F                                                                                                                                                   |
| CERTIFICATES                         | CB, ENEC, EPD, RCM                                                                                                                                  |
| Lightsource info                     |                                                                                                                                                     |
| LIGHTSOURCE NAME                     | LED                                                                                                                                                 |
| LIGHTSOURCE                          | LED cluster 14,4W / CRI>90 (R9: 50) / 2700K / 1644lm                                                                                                |
| TM-30 VALUES                         | Rf: 91 / Rg: 100                                                                                                                                    |
| SDCM                                 | SDCM3                                                                                                                                               |
| RISKGROUP                            | RG2                                                                                                                                                 |
| LM80                                 | L80 > 150000                                                                                                                                        |
| BEAMANGLE                            | 40°                                                                                                                                                 |
| LED TECHNICS (LIGHT SOURCE)          | 1644lm // 14,4W // 111lm/W                                                                                                                          |
| LED TECHNICS (LUMINAIRE)             | 1097lm // 16,6W // 66lm/W                                                                                                                           |
| Requirements                         |                                                                                                                                                     |
| LOGIC LINEAR BOX                     |                                                                                                                                                     |

For detailed installation instructions, please consult the manual : [30811\\_XXX5\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Ground mounting boxes




**30810 0010** LOGIC LINEAR 440 BOX

☐

Cutout dimension (mm): 480 x 150

Waterproof connection parts



**21034 0150** IP68 Y-CONNECTOR 5P

☐

Notes: