





INFORM 40 SQ 320 DOWN-UP TW 2 DT8 85063 DIM5

30726 8035 B-B

AVAILABLE IN

BLACK-BLACK 30726 8035 B-B

WHITE-BLACK 30726 8035 W-B



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	5.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.2 x DIMMABLE LED POWER SUPPLY (DALI DT8) 2 drivers for DOWN and UP INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0,75mm ² 1,6m MELANOPIC LIGHT TECHNOLOGY

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN @ 2700K: LED cluster 29,8W / CRI>80 (R9: 50) / 2700K-5000K / 3904lm UP @ 2700K: LED cluster 29,8W / CRI>80 (R9: 50) / 2700K-5000K / 3904lm Or DOWN @ 5000K: LED cluster 27W / CRI>80 (R9: 50) / 2700K-5000K / 4672lm UP @ 5000K: LED cluster 27W / CRI>80 (R9: 50) / 2700K-5000K / 4672lm
SDCM	SDCM3
RISKGROUP	RG1
LM80	L80 > 60000
BEAMANGLE	63°
LED TECHNICS (LIGHT SOURCE)	DOWN @ 2700K: 3904lm // 29,8W // 131lm/W UP @ 2700K: 3904lm // 29,8W // 131lm/W Or DOWN @ 5000K: 4672lm // 27W // 173lm/W UP @ 5000K: 4672lm // 27W // 173lm/W
LED TECHNICS (LUMINAIRE)	DOWN @ 2700K: 2701lm // 34,3W // 79lm/W UP @ 2700K: 2571lm // 34,3W // 75lm/W Or DOWN @ 5000K: 3233lm // 31W // 104lm/W UP @ 5000K: 3077lm // 31W // 99lm/W

Options

CABLE BASE R / S

For detailed installation instructions, please consult the manual : [30726_XXX5_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

Notes: