



## MINIGRID ON 350 93018 DIM8

100046 9318 B-B



AVAILABLE IN

**BLACK-BLACK** 100046 9318 B-B

**BLACK-WHITE** 100046 9318 B-W

**WHITE-BLACK** 100046 9318 W-B

**WHITE-WHITE** 100046 9318 W-W



[View on website](#)




| General info                |                                                                 |
|-----------------------------|-----------------------------------------------------------------|
| LOCATION                    | indoor                                                          |
| INSTALLATION                | Ceiling Surface mounted                                         |
| INGRESS PROTECTION          | IP20                                                            |
| WEIGHT (KG)                 | 2.6                                                             |
| ADJUSTABILITY               | 0° to 20° swiveling, 350° rotatable                             |
| INFORMATION                 | 3 x REFLECTOR SP-18°<br>INCL.DIMMABLE LED POWER SUPPLY 500mA-DC |
| Electrical info             |                                                                 |
| ELECTRICAL                  | 220-240V / 50-60Hz                                              |
| CLASS                       | II                                                              |
| POWER SUPPLY                | YES                                                             |
| DIM TYPE                    | mains (phase cut-off)                                           |
| ENERGY CLASS                | E                                                               |
| Lightsource info            |                                                                 |
| LIGHTSOURCE NAME            | LED                                                             |
| LIGHTSOURCE                 | 3 x (LED array 8,6W / CRI>90 (R9: 52) / 3000K / 1089lm)         |
| TM-30 VALUES                | rf: 90 / Rg: 99                                                 |
| SDCM                        | SDCM1                                                           |
| RISKGROUPE                  | RG1                                                             |
| LM80                        | L90B10 > 50000                                                  |
| BEAMANGLE                   | 18°                                                             |
| LED TECHNICS (LIGHT SOURCE) | 3267lm // 25,8W // 127lm/W                                      |
| LED TECHNICS (LUMINAIRE)    | 2710lm // 29,7W // 91lm/W                                       |

For detailed installation instructions, please consult the manual : [100046\\_XXX8\\_HAND.pdf](#)

FINISH YOUR SPECIFICATION

Miscellaneous control equipment



**300 90 004 ED8** WIRELESS CONTROL DIM8

Dimtype: WDL = wireless dimmable

Cutout dimension (mm): 40



Notes: