



## M20/M26H - OBIN 92724 MDL

30513 9220 BRA

AVAILABLE IN

**BLACK** 30513 9220 B

**BRUSHED ALU** 30513 9220 BRA

**BRUSHED ANTHRACITE** 30513 9220 BRAT



**BRUSHED BROWN BRONZE** 30513 9220 BRBB

**BRUSHED GOLD** 30513 9220 BRG

**BRUSHED OLD BRONZE** 30513 9220 BROB

**CREAM** 30513 9220 CR

**WHITE** 30513 9220 W



 [View on website](#)



### General info

<b>LOCATION</b>	indoor
<b>INSTALLATION</b>	Low voltage systems Low voltage system mounted
<b>INGRESS PROTECTION</b>	IP20
<b>WEIGHT (KG)</b>	0.5
<b>ADJUSTABILITY</b>	0° to 45° swiveling, 360° rotatable
<b>INFORMATION</b>	LENS FL-24° EXCL.LED POWER SUPPLY 48V-DC

### Electrical info

<b>ELECTRICAL</b>	48V-DC
<b>CLASS</b>	III
<b>DIM TYPE</b>	MDL = 1-10V or DALI or push button
<b>ENERGY CLASS</b>	E
<b>CERTIFICATES</b>	CB, ENEC

### Lightsource info

<b>LIGHTSOURCE NAME</b>	LED
<b>LIGHTSOURCE</b>	LED array 11,6W / CRI>90 (R9: 60) / 2700K / 1458lm
<b>TM-30 VALUES</b>	rf: 89 / Rg: 100
<b>SDCM</b>	SDCM1
<b>RISKGROUP</b>	RG1
<b>LM80</b>	L90B10 > 50000
<b>BEAMANGLE</b>	24°
<b>LED TECHNICS (LIGHT SOURCE)</b>	1458lm // 11,6W // 125lm/W
<b>LED TECHNICS (LUMINAIRE)</b>	1217lm // 13,3W // 91lm/W

### Requirements

SPY 90 TUBE  
LED POWER SUPPLY 48V-DC

### Options

DIMMABLE MODULATOR

### Accessories

HONEYCOMB 75

# DELTALIGHT

## M20/M26H - OBIN 92724 MDL


30513 9220 BRA

For detailed installation instructions, please consult the manual : [30513\\_XXX0\\_HAND.pdf](#)

### FINISH YOUR SPECIFICATION

#### Current supply

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current




**21032 0030** SMART 48 MODULATOR PLUG-IN WD

14

Dimtype: WDL = wireless dimmable

#### SMART 48

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.


Min current | Max current



**300 90 011** SMART 48 MODULATOR DIM9

14

Dimtype: 1-10V or DALI or push button




**300 90 012** SMART 48 MODULATOR WD

14

Dimtype: WDL = wireless dimmable

#### LED power supplies

#### # of Fixtures

 # of fixtures indicates how many devices can be connected (min -> max) to the power supply. The values before and after the '|' correspond respectively with the minimum and maximum driving current. Values between brackets are applicable to 110V.

Min current | Max current



**300 89 48 100** LED POWER SUPPLY 48V-DC / 100W DIN

7

Dimtype: non-dimmable

# DELTALIGHT

## M20/M26H - OBIN 92724 MDL

30513 9220 BRA



**300 89 48 240** LED POWER SUPPLY 48V-DC / 240W DIN

14



**Dimtype: non-dimmable**




**21012 0230** LED POWER SUPPLY 48V-DC / 100W

7



**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**



**21012 0240** LED POWER SUPPLY 48V-DC / 200W

14



**Dimtype: non-dimmable**

**Cutout dimension (mm): 40**

### Light altering devices



**19810 0110 B** HONEYCOMB 75 SINGLE USE B




# DELTALIGHT

## M20/M26H - OBIN 92724 MDL

30513 9220 BRA

### Finish your product



**19810 0170 B** SPY 90 TUBE B

**19810 0170 CR** SPY 90 TUBE CR

**19810 0170 DC** SPY 90 TUBE DC

**19810 0170 FBR** SPY 90 TUBE FBR

**19810 0170 FG** SPY 90 TUBE FG

**19810 0170 GC** SPY 90 TUBE GC


**19810 0170 PB** SPY 90 TUBE PB

**19810 0170 W** SPY 90 TUBE W


## COMPATIBLE COMPOSABLES

### SHIFTLINE M26H profile


### Available Colours



**23359 0000** SLM26H - PROFILE



**23359 0010** SLM26H - PROFILE 1m




**23359 0020** SLM26H - PROFILE 2m



# DELTALIGHT

## M20/M26H - OBIN 92724 MDL

30513 9220 BRA



**23359 0030** SLM26H - PROFILE 3m



### SPLITLINE M20 ST profile

Available Colours



**23397 0000** SPM20 ST - PROFILE



**23397 0020** SPM20 ST - PROFILE 2m




**23397 0030** SPM20 ST - PROFILE 3m




### SPLITLINE M20 profile


Available Colours




**420 20 10 00** SPM20 - PROFILE 1m



**420 20 20 00** SPM20 - PROFILE 2m



**420 20 30 00** SPM20 - PROFILE 3m



**23301 0000** SPM20 - PROFILE B



Notes: